
python-ldap Documentation

Release 3.4.3

python-ldap project

September 20, 2022

Contents

1	What is python-ldap?	1
2	Get it!	3
3	Mailing list	5
4	Documentation	7
5	Contents	9
5.1	Installing python-ldap	9
5.2	Bytes/text management	12
5.3	python-ldap Reference Documentation	13
5.4	Third-party documentation	56
5.5	Contributing to python-ldap	57
5.6	python-ldap FAQ	61
6	Indices and tables	65
	Python Module Index	67
	Index	69

What is python-ldap?

python-ldap provides an object-oriented API to access [LDAP](#) directory servers from [Python](#) programs.

For LDAP operations the module wraps [OpenLDAP](#)'s client library, *libldap*.

Additionally, the package contains modules for other LDAP-related stuff:

- [LDIF](#) parsing and generation
- LDAP URLs
- LDAPv3 subschema

CHAPTER 2

Get it!

Installation instructions are available for several platforms.

Source code can be obtained using Git:

```
git clone https://github.com/python-ldap/python-ldap
```


CHAPTER 3

Mailing list

Discussion about the use and future of `python-ldap` occurs in the `python-ldap@python.org` mailing list. You can [subscribe](#) or [unsubscribe](#) to this list or browse the [list archive](#).

CHAPTER 4

Documentation

The documentation for python-ldap 3.x is hosted at [Read the Docs](#).

You can switch between versions of the library, or download PDF or HTML versions for offline use, using the sidebar on the right.

Documentation for some older versions is available for download at the [GitHub release page](#).

5.1 Installing python-ldap

5.1.1 Installing from PyPI

The preferred point for downloading the “official” source distribution is the [PyPI repository](#) which supports installing via `pip`. For example:

```
$ python -m pip install python-ldap
```

For installing from PyPI, you will need the same *Build prerequisites* as when installing from source.

We do not currently provide pre-built packages (wheels).

Furthermore, python-ldap requires the modules `pyasn1` and `pyasn1-modules`. `pip` will install these automatically.

5.1.2 Pre-built Binaries

Because distributions seem to be all over the place, this page tries to list all the current ones we know of.

Note that the python-ldap team is not responsible for the binary packages except the sources you can grab from the PyPI page. Also note that binary packages are most times not up to date. If you experience troubles with a binary package, it would be nice if you try to build a recent version of python-ldap before submitting a bug report to make sure you did not hit a problem already fixed in recent releases.

openSUSE Linux

Ships with python-ldap and there’s an additional [download repository](#) which contains builds of latest releases (see also [OBS package](#)).

Debian Linux

Have a look into the [Debian Package Tracker](#) to get up to date information which versions are available.

Windows

Unofficial packages for Windows are available on [Christoph Gohlke's page](#).

FreeBSD

The CVS repository of FreeBSD contains the package `py-ldap`

macOS

You can install directly with pip:

```
$ xcode-select --install
$ pip install python-ldap \
  --global-option=build_ext \
  --global-option="-I$(xcrun --show-sdk-path)/usr/include/sasl"
```

5.1.3 Installing from Source

`python-ldap` is built and installed using the Python `setuptools`. From a source repository:

```
$ python -m pip install setuptools
$ python setup.py install
```

If you have more than one Python interpreter installed locally, you should use the same one you plan to use `python-ldap` with.

Further instructions can be found in [Setuptools documentation](#).

5.1.4 Build prerequisites

The following software packages are required to be installed on the local system when building `python-ldap`:

- [Python](#) including its development files
- C compiler corresponding to your Python version (on Linux, it is usually `gcc`)
- [OpenLDAP](#) client libs version 2.4.11 or later; it is not possible and not supported to build with prior versions.
- [OpenSSL](#) (optional)
- [Cyrus SASL](#) (optional)
- Kerberos libraries, MIT or Heimdal (optional)

Alpine

Packages for building:

```
# apk add build-base openldap-dev python3-dev
```

CentOS

Packages for building:

```
# yum groupinstall "Development tools"
# yum install openldap-devel python-devel
```

Debian

Packages for building and testing:

```
# apt-get install build-essential python3-dev \
    libldap2-dev libsasl2-dev slapd ldap-utils tox \
    lcov valgrind
```

Note: On older releases `tox` was called `python-tox`.

Fedora

Packages for building and testing:

```
# dnf install "@C Development Tools and Libraries" openldap-devel \
    python3-devel python3-tox \
    lcov clang-analyzer valgrind
```

Note: `openldap-2.4.45-2` (Fedora 26), `openldap-2.4.45-4` (Fedora 27) or newer are required.

5.1.5 `setup.cfg`

The file `setup.cfg` allows to set some build and installation parameters for reflecting the local installation of required software packages. Only section `[_ldap]` is described here. More information about other sections can be found in [Setuptools documentation](#).

library_dirs

Specifies in which directories to search for required libraries.

include_dirs

Specifies in which directories to search for include files of required libraries.

libs

A space-separated list of library names to link to (see *Libraries used*).

extra_compile_args

Compiler options.

`extra_objects`

Libraries used

`ldap`

`ldap_r`

The LDAP protocol library of OpenLDAP. `ldap_r` is the reentrant version and should be preferred.

`lber`

The BER encoder/decoder library of OpenLDAP.

`sasl2`

The Cyrus-SASL library (optional)

`ssl`

The SSL/TLS library of OpenSSL (optional)

`crypto`

The basic cryptographic library of OpenSSL (optional)

Example

The following example is for a full-featured build (including SSL and SASL support) of python-ldap with OpenLDAP installed in a different prefix directory (here `/opt/openldap-2.4`) and SASL header files found in `/usr/include/sasl`. Debugging symbols are preserved with compile option `-g`.

```
[_ldap]
library_dirs = /opt/openldap-2.4/lib
include_dirs = /opt/openldap-2.4/include /usr/include/sasl

extra_compile_args = -g
extra_objects =

libs = ldap_r lber sasl2 ssl crypto
```

5.2 Bytes/text management

The LDAP protocol states that some fields (distinguished names, relative distinguished names, attribute names, queries) be encoded in UTF-8. In python-ldap, these are represented as text (`str` on Python 3).

Attribute *values*, on the other hand, **MAY** contain any type of data, including text. To know what type of data is represented, python-ldap would need access to the schema, which is not always available (nor always correct). Thus, attribute values are *always* treated as `bytes`. Encoding/decoding to other formats – text, images, etc. – is left to the caller.

5.2.1 Historical note

Python 3 introduced a hard distinction between *text* (`str`) – sequences of characters (formally, *Unicode codepoints*) – and *bytes* – sequences of 8-bit values used to encode *any* kind of data for storage or transmission.

Python 2 had the same distinction between `str` (bytes) and `unicode` (text). However, values could be implicitly converted between these types as needed, e.g. when comparing or writing to disk or the network. The implicit encoding and decoding can be a source of subtle bugs when not designed and tested adequately.

In python-ldap 2.x (for Python 2), bytes were used for all fields, including those guaranteed to be text.

From version 3.0 to 3.3, python-ldap uses text where appropriate. On Python 2, special `bytes_mode` and `bytes_strictness` settings influenced how text was handled.

From version 3.3 on, only Python 3 is supported. The “bytes mode” settings are deprecated and do nothing.

5.3 python-ldap Reference Documentation

This document describes the package python-ldap with its various modules.

Depending on what you want to do this manual assumes basic to expert knowledge about the Python language and the LDAP standard (LDAPv3).

5.3.1 ldap LDAP library interface module

This module provides access to the LDAP (Lightweight Directory Access Protocol) C API implemented in OpenLDAP. It is similar to the C API, with the notable differences that lists are manipulated via Python list operations and errors appear as exceptions.

See also:

For more detailed information on the C interface, please see the (expired) [draft-ietf-ldapext-ldap-c-api](#)

This documentation is current for the Python LDAP module, version 3.4.3. Source and binaries are available from <https://www.python-ldap.org/>.

Functions

This module defines the following functions:

```
ldap.initialize(uri[, trace_level=0[, trace_file=sys.stdout[, trace_stack_limit=None[, fileno=None ]]]]) → LDAPObject object
```

Initializes a new connection object for accessing the given LDAP server, and return an *LDAPObject* used to perform operations on that server.

The *uri* parameter may be a comma- or whitespace-separated list of URIs containing only the schema, the host, and the port fields. Note that when using multiple URIs you cannot determine to which URI your client gets connected.

If *fileno* parameter is given then the file descriptor will be used to connect to an LDAP server. The *fileno* must either be a socket file descriptor as `int` or a file-like object with a *fileno()* method that returns a socket file descriptor. The socket file descriptor must already be connected. *LDAPObject* does not take ownership of the file descriptor. It must be kept open during operations and explicitly closed after the *LDAPObject* is unbound. The internal connection type is determined from the URI, TCP for `ldap://` / `ldaps://`, IPC (AF_UNIX) for `ldapi://`. The parameter is not available on macOS when python-ldap is compiled with system libldap, see `INIT_FD_AVAIL`.

Note that internally the OpenLDAP function `ldap_initialize(3)` is called which just initializes the LDAP connection struct in the C API - nothing else. Therefore the first call to an operation method (bind, search etc.) then really opens the connection (lazy connect). Before that nothing is sent on the wire. The error handling in the calling application has to correctly handle this behaviour.

Three optional arguments are for generating debug log information: *trace_level* specifies the amount of information being logged, *trace_file* specifies a file-like object as target of the debug log and *trace_stack_limit* specifies the stack limit of tracebacks in debug log.

Possible values for *trace_level* are 0 for no logging, 1 for only logging the method calls with arguments, 2 for logging the method calls with arguments and the complete results and 9 for also logging the traceback of method calls.

This function is a thin wrapper around instantiating *LDAPObject*. Any additional keyword arguments are passed to *LDAPObject*. It is also fine to instantiate a *LDAPObject* (or a subclass) directly.

The function additionally takes *bytes_mode* and *bytes_strictness* keyword arguments, which are deprecated and ignored. See *Bytes/text management* for details.

See also:

RFC 4516 - Lightweight Directory Access Protocol (LDAP): Uniform Resource Locator

New in version 3.3: The *fileno* argument was added.

Deprecated since version 3.4: *bytes_mode* and *bytes_strictness* arguments are deprecated.

`ldap.get_option(option) → int|string`

This function returns the value of the global option specified by *option*.

`ldap.set_option(option, invalue) → None`

This function sets the value of the global option specified by *option* to *invalue*.

Note: Most global settings do not affect existing *LDAPObject* connections. Applications should call *set_option()* before they establish connections with *initialize()*.

Changed in version 3.1: The deprecated functions `ldap.init()` and `ldap.open()` were removed.

Constants

The module defines various constants. Note that some constants depend on the build options and which underlying libs were used or even on the version of the libs. So before using those constants the application has to explicitly check whether they are available.

General

`ldap.PORT`

The assigned TCP port number (389) that LDAP servers listen on.

`ldap.SASL_AVAIL`

Integer where a non-zero value indicates that python-ldap was built with support for SASL (Cyrus-SASL).

`ldap.TLS_AVAIL`

Integer where a non-zero value indicates that python-ldap was built with support for SSL/TLS (OpenSSL or similar libs).

`ldap.INIT_FD_AVAIL`

Integer where a non-zero value indicates that python-ldap supports *initialize()* from a file descriptor. The feature is generally available except on macOS when python-ldap is compiled with system libldap.

Options

See also:

`ldap.conf(5)` and `ldap_get_option(3)`

For use with functions `set_option()` and `get_option()` and methods `LDAPObject.set_option()` and `LDAPObject.get_option()` the following option identifiers are defined as constants:

`ldap.OPT_API_FEATURE_INFO`

`ldap.OPT_API_INFO`

`ldap.OPT_CLIENT_CONTROLS`

`ldap.OPT_DEBUG_LEVEL`

Sets the debug level within the underlying OpenLDAP C lib (libldap). libldap sends the log messages to stderr.

`ldap.OPT_DEFBASE`

`ldap.OPT_DEREF`

Specifies how alias dereferencing is done within the underlying LDAP C lib.

`ldap.OPT_ERROR_STRING`

`ldap.OPT_DIAGNOSTIC_MESSAGE`

`ldap.OPT_HOST_NAME`

`ldap.OPT_MATCHED_DN`

`ldap.OPT_NETWORK_TIMEOUT`

Changed in version 3.0: A timeout of `-1` or `None` resets timeout to infinity.

`ldap.OPT_PROTOCOL_VERSION`

Sets the LDAP protocol version used for a connection. This is mapped to object attribute `ldap.LDAPObject.protocol_version`

`ldap.OPT_REFERRALS`

int specifying whether referrals should be automatically chased within the underlying LDAP C lib.

`ldap.OPT_REFHOPLIMIT`

`ldap.OPT_RESTART`

`ldap.OPT_SERVER_CONTROLS`

`ldap.OPT_SIZELIMIT`

`ldap.OPT_SUCCESS`

`ldap.OPT_TIMELIMIT`

`ldap.OPT_TIMEOUT`

Changed in version 3.0: A timeout of `-1` or `None` resets timeout to infinity.

`ldap.OPT_URI`

SASL options

Unlike most other options, SASL options must be set on an `LDAPObject` instance.

`ldap.OPT_X_SASL_AUTHCID`

`ldap.OPT_X_SASL_AUTHZID`

`ldap.OPT_X_SASL_MECH`

`ldap.OPT_X_SASL_NOCANON`

If set to zero, SASL host name canonicalization is disabled.

`ldap.OPT_X_SASL_REALM`

`ldap.OPT_X_SASL_SECPROPS`

`ldap.OPT_X_SASL_SSF`

`ldap.OPT_X_SASL_SSF_EXTERNAL`

`ldap.OPT_X_SASL_SSF_MAX`

`ldap.OPT_X_SASL_SSF_MIN`

TLS options

Warning: libldap does not materialize all TLS settings immediately. You must use `OPT_X_TLS_NEWCTX` with value 0 to instruct libldap to apply pending TLS settings and create a new internal TLS context:

```
conn = ldap.initialize("ldap://ldap.example")
conn.set_option(ldap.OPT_X_TLS_CACERTFILE, '/path/to/ca.pem')
conn.set_option(ldap.OPT_X_TLS_NEWCTX, 0)
conn.start_tls_s()
conn.simple_bind_s(dn, password)
```

`ldap.OPT_X_TLS_NEWCTX`

set and apply TLS settings to internal TLS context. Value 0 creates a new client-side context.

`ldap.OPT_X_TLS_PACKAGE`

Get TLS implementation, known values are

- GnuTLS
- MozNSS (Mozilla NSS)
- OpenSSL

`ldap.OPT_X_TLS_CACERTDIR`

get/set path to directory with CA certs

`ldap.OPT_X_TLS_CACERTFILE`

get/set path to PEM file with CA certs

`ldap.OPT_X_TLS_CERTFILE`

get/set path to file with PEM encoded cert for client cert authentication, requires `OPT_X_TLS_KEYFILE`.

`ldap.OPT_X_TLS_KEYFILE`

get/set path to file with PEM encoded key for client cert authentication, requires `OPT_X_TLS_CERTFILE`.

`ldap.OPT_X_TLS_CRLCHECK`

get/set certificate revocation list (CRL) check mode. CRL validation requires `OPT_X_TLS_CRLFILE`.

`OPT_X_TLS_CRL_NONE` Don't perform CRL checks

`OPT_X_TLS_CRL_PEER` Perform CRL check for peer's end entity cert.

`OPT_X_TLS_CRL_ALL` Perform CRL checks for the whole cert chain

`ldap.OPT_X_TLS_CRLFILE`

get/set path to CRL file

`ldap.OPT_X_TLS_CRL_ALL`

value for `OPT_X_TLS_CRLCHECK`

- `ldap.OPT_X_TLS_CRL_NONE`
value for `OPT_X_TLS_CRLCHECK`
- `ldap.OPT_X_TLS_CRL_PEER`
value for `OPT_X_TLS_CRLCHECK`
- `ldap.OPT_X_TLS_REQUIRE_CERT`
get/set validation strategy for server cert.
- `OPT_X_TLS_NEVER` Don't check server cert and host name
- `OPT_X_TLS_ALLOW` Used internally by slapd server.
- `OPT_X_TLS_DEMAND` Validate peer cert chain and host name
- `OPT_X_TLS_HARD` Same as `OPT_X_TLS_DEMAND`
- `ldap.OPT_X_TLS_REQUIRE_SAN`
get/set how OpenLDAP validates subject alternative name extension, available in OpenLDAP 2.4.52 and newer.
- `OPT_X_TLS_NEVER` Don't check SAN
- `OPT_X_TLS_ALLOW` Check SAN first, always fall back to subject common name (default)
- `OPT_X_TLS_TRY` Check SAN first, only fall back to subject common name, when no SAN extension is present (**RFC 6125** conform validation)
- `OPT_X_TLS_DEMAND` Validate peer cert chain and host name
- `OPT_X_TLS_HARD` Require SAN, don't fall back to subject common name
- New in version 3.4.0.
- `ldap.OPT_X_TLS_ALLOW`
Value for `OPT_X_TLS_REQUIRE_CERT` and `OPT_X_TLS_REQUIRE_SAN`
- `ldap.OPT_X_TLS_DEMAND`
Value for `OPT_X_TLS_REQUIRE_CERT` and `OPT_X_TLS_REQUIRE_SAN`
- `ldap.OPT_X_TLS_HARD`
Value for `OPT_X_TLS_REQUIRE_CERT` and `OPT_X_TLS_REQUIRE_SAN`
- `ldap.OPT_X_TLS_NEVER`
Value for `OPT_X_TLS_REQUIRE_CERT` and `OPT_X_TLS_REQUIRE_SAN`
- `ldap.OPT_X_TLS_TRY`
Value for `OPT_X_TLS_REQUIRE_CERT`
- Deprecated since version 3.3.0: This value is only used by slapd server internally. It will be removed in the future.
- `ldap.OPT_X_TLS_CIPHER`
get cipher suite name from TLS session
- `ldap.OPT_X_TLS_CIPHER_SUITE`
get/set allowed cipher suites
- `ldap.OPT_X_TLS_CTX`
get address of internal memory address of TLS context (**DO NOT USE**)
- `ldap.OPT_X_TLS_PEER_CERT`
Get peer's certificate as binary ASN.1 data structure (DER)
- New in version 3.4.1.

Note: The option leaks memory with OpenLDAP < 2.5.8.

- `ldap.OPT_X_TLS_PROTOCOL_MIN`
get/set minimum protocol version (wire protocol version as int)
- `ldap.OPT_X_TLS_PROTOCOL_MAX`
get/set maximum protocol version (wire protocol version as int), available in OpenLDAP 2.5 and newer.
New in version 3.4.1.
- `ldap.OPT_X_TLS_PROTOCOL_SSL3`
Value for `OPT_X_TLS_PROTOCOL_MIN` and `OPT_X_TLS_PROTOCOL_MAX`, represents SSL 3
New in version 3.4.1.
- `ldap.OPT_X_TLS_PROTOCOL_TLS1_0`
Value for `OPT_X_TLS_PROTOCOL_MIN` and `OPT_X_TLS_PROTOCOL_MAX`, represents TLS 1.0
New in version 3.4.1.
- `ldap.OPT_X_TLS_PROTOCOL_TLS1_1`
Value for `OPT_X_TLS_PROTOCOL_MIN` and `OPT_X_TLS_PROTOCOL_MAX`, represents TLS 1.1
New in version 3.4.1.
- `ldap.OPT_X_TLS_PROTOCOL_TLS1_2`
Value for `OPT_X_TLS_PROTOCOL_MIN` and `OPT_X_TLS_PROTOCOL_MAX`, represents TLS 1.2
New in version 3.4.1.
- `ldap.OPT_X_TLS_PROTOCOL_TLS1_3`
Value for `OPT_X_TLS_PROTOCOL_MIN` and `OPT_X_TLS_PROTOCOL_MAX`, represents TLS 1.3
New in version 3.4.1.
- `ldap.OPT_X_TLS_VERSION`
Get negotiated TLS protocol version as string
- `ldap.OPT_X_TLS_RANDOM_FILE`
get/set path to /dev/urandom (**DO NOT USE**)
- `ldap.OPT_X_TLS`
Deprecated since version 3.3.0: The option is deprecated in OpenLDAP and should no longer be used. It will be removed in the future.

Note: OpenLDAP supports several TLS/SSL libraries. OpenSSL is the most common backend. Some options may not be available when libldap uses NSS, GnuTLS, or Apple's Secure Transport backend.

Keepalive options

- `ldap.OPT_X_KEEPALIVE_IDLE`
- `ldap.OPT_X_KEEPALIVE_PROBES`
- `ldap.OPT_X_KEEPALIVE_INTERVAL`

DN format flags

This constants are used for DN-parsing functions found in sub-module `ldap.dn`.

See also:

`ldap_str2dn(3)`

`ldap.DN_FORMAT_LDAP`

`ldap.DN_FORMAT_LDAPV3`

`ldap.DN_FORMAT_LDAPV2`

`ldap.DN_FORMAT_DCE`

`ldap.DN_FORMAT_UFN`

`ldap.DN_FORMAT_AD_CANONICAL`

`ldap.DN_FORMAT_MASK`

`ldap.DN_PRETTY`

`ldap.DN_SKIP`

`ldap.DN_P_NOLEADTRAILSPACES`

`ldap.DN_P_NOSPACEAFTERRDN`

`ldap.DN_PEDANTIC`

Exceptions

The module defines the following exceptions:

exception `ldap.LDAPError`

This is the base class of all exceptions raised by the module `ldap`. Unlike the C interface, errors are not returned as result codes, but are instead turned into exceptions, raised as soon as the error condition is detected.

The exceptions are accompanied by a dictionary with additional information. All fields are optional and more fields may be added in the future. Currently, `python-ldap` may set the following fields:

- 'result': a numeric code of the error class.
- 'desc': string giving a description of the error class, as provided by calling OpenLDAP's `ldap_err2string` on the result.
- 'info': string containing more information that the server may have sent. The value is server-specific: for example, the OpenLDAP server may send different info messages than Active Directory or 389-DS.
- 'matched': truncated form of the name provided or alias. dereferenced for the lowest entry (object or alias) that was matched.
- 'msgid': ID of the matching asynchronous request. This can be used in asynchronous code where `result()` raises the result of an operation as an exception. For example, this is the case for `compare()`, always raises the boolean result as an exception (`COMPARE_TRUE` or `COMPARE_FALSE`).
- 'ctrls': list of `ldap.controls.LDAPControl` instances attached to the error.
- 'errno': the C `errno`, usually set by system calls or `libc` rather than the LDAP libraries.

exception `ldap.ADMINLIMIT_EXCEEDED`

exception `ldap.AFFECTS_MULTIPLE_DSAS`

exception ldap.**ALIAS_DEREF_PROBLEM**

A problem was encountered when dereferencing an alias. (Sets the `matched` field.)

exception ldap.**ALIAS_PROBLEM**

An alias in the directory points to a nonexistent entry. (Sets the `matched` field.)

exception ldap.**ALREADY_EXISTS**

The entry already exists. E.g. the `dn` specified with `add()` already exists in the DIT.

exception ldap.**AUTH_UNKNOWN**

The authentication method specified to `bind()` is not known.

exception ldap.**BUSY**

The DSA is busy.

exception ldap.**CLIENT_LOOP**

exception ldap.**COMPARE_FALSE**

A compare operation returned false. (This exception should only be seen asynchronous operations, because `compare_s()` returns a boolean result.)

exception ldap.**COMPARE_TRUE**

A compare operation returned true. (This exception should only be seen asynchronous operations, because `compare_s()` returns a boolean result.)

exception ldap.**CONFIDENTIALITY_REQUIRED**

Indicates that the session is not protected by a protocol such as Transport Layer Security (TLS), which provides session confidentiality.

exception ldap.**CONNECT_ERROR**

exception ldap.**CONSTRAINT_VIOLATION**

An attribute value specified or an operation started violates some server-side constraint (e.g., a postalAddress has too many lines or a line that is too long or a password is expired).

exception ldap.**CONTROL_NOT_FOUND**

exception ldap.**DECODING_ERROR**

An error was encountered decoding a result from the LDAP server.

exception ldap.**ENCODING_ERROR**

An error was encountered encoding parameters to send to the LDAP server.

exception ldap.**FILTER_ERROR**

An invalid filter was supplied to `search()` (e.g. unbalanced parentheses).

exception ldap.**INAPPROPRIATE_AUTH**

Inappropriate authentication was specified (e.g. `AUTH_SIMPLE` was specified and the entry does not have a `userPassword` attribute).

exception ldap.**INAPPROPRIATE_MATCHING**

Filter type not supported for the specified attribute.

exception ldap.**INSUFFICIENT_ACCESS**

The user has insufficient access to perform the operation.

exception ldap.**INVALID_CREDENTIALS**

Invalid credentials were presented during `bind()` or `simple_bind()`. (e.g., the wrong password).

exception ldap.**INVALID_DN_SYNTAX**

A syntactically invalid DN was specified. (Sets the `matched` field.)

exception ldap.**INVALID_SYNTAX**

An attribute value specified by the client did not comply to the syntax defined in the server-side schema.

exception ldap.IS_LEAF

The object specified is a leaf of the directory tree. Sets the `matched` field of the exception dictionary value.

exception ldap.LOCAL_ERROR

Some local error occurred. This is usually due to failed memory allocation.

exception ldap.LOOP_DETECT

A loop was detected.

exception ldap.MORE_RESULTS_TO_RETURN**exception ldap.NAMING_VIOLATION**

A naming violation occurred. This is raised e.g. if the LDAP server has constraints about the tree naming.

exception ldap.NO_OBJECT_CLASS_MODS

Modifying the `objectClass` attribute as requested is not allowed (e.g. modifying structural object class of existing entry).

exception ldap.NOT_ALLOWED_ON_NONLEAF

The operation is not allowed on a non-leaf object.

exception ldap.NOT_ALLOWED_ON_RDN

The operation is not allowed on an RDN.

exception ldap.NOT_SUPPORTED**exception ldap.NO_MEMORY****exception ldap.NO_RESULTS_RETURNED****exception ldap.NO_SUCH_ATTRIBUTE**

The attribute type specified does not exist in the entry.

exception ldap.NO_SUCH_OBJECT

The specified object does not exist in the directory. Sets the `matched` field of the exception dictionary value.

exception ldap.OBJECT_CLASS_VIOLATION

An object class violation occurred when the LDAP server checked the data sent by the client against the server-side schema (e.g. a “must” attribute was missing in the entry data).

exception ldap.OPERATIONS_ERROR

An operations error occurred.

exception ldap.OTHER

An unclassified error occurred.

exception ldap.PARAM_ERROR

An ldap routine was called with a bad parameter.

exception ldap.PARTIAL_RESULTS

Partial results only returned. This exception is raised if a referral is received when using LDAPv2. (This exception should never be seen with LDAPv3.)

exception ldap.PROTOCOL_ERROR

A violation of the LDAP protocol was detected.

exception ldap.RESULTS_TOO_LARGE

The result does not fit into a UDP packet. This happens only when using UDP-based CLDAP (connection-less LDAP) which is not supported anyway.

exception ldap.SASL_BIND_IN_PROGRESS**exception ldap.SERVER_DOWN**

The LDAP library can't contact the LDAP server.

exception `ldap.SIZELIMIT_EXCEEDED`

An LDAP size limit was exceeded. This could be due to a `sizelimit` configuration on the LDAP server.

exception `ldap.STRONG_AUTH_NOT_SUPPORTED`

The LDAP server does not support strong authentication.

exception `ldap.STRONG_AUTH_REQUIRED`

Strong authentication is required for the operation.

exception `ldap.TIMELIMIT_EXCEEDED`

An LDAP time limit was exceeded.

exception `ldap.TIMEOUT`

A timelimit was exceeded while waiting for a result from the server.

exception `ldap.TYPE_OR_VALUE_EXISTS`

An attribute type or attribute value specified already exists in the entry.

exception `ldap.UNAVAILABLE`

The DSA is unavailable.

exception `ldap.UNAVAILABLE_CRITICAL_EXTENSION`

Indicates that the LDAP server was unable to satisfy a request because one or more critical extensions were not available. Either the server does not support the control or the control is not appropriate for the operation type.

exception `ldap.UNDEFINED_TYPE`

An attribute type used is not defined in the server-side schema.

exception `ldap.UNWILLING_TO_PERFORM`

The DSA is unwilling to perform the operation.

exception `ldap.USER_CANCELLED`

The operation was cancelled via the `abandon()` method.

The above exceptions are raised when a result code from an underlying API call does not indicate success.

Warnings

class `ldap.LDAPBytesWarning`

This warning is deprecated. `python-ldap` no longer raises it.

It used to be raised under Python 2 when bytes/text mismatch in non-strict bytes mode. See *Bytes/text management* for details.

New in version 3.0.0.

Changed in version 3.4.0: Deprecated.

LDAPObject classes

class `ldap.ldapobject.LDAPObject`

Instances of `LDAPObject` are returned by `initialize()`. The connection is automatically unbound and closed when the LDAP object is deleted.

`LDAPObject` is an alias of `SimpleLDAPObject`, the default connection class. If you wish to use a different class, instantiate it directly instead of calling `initialize()`.

(It is also possible, but not recommended, to change the default by setting `ldap.ldapobject.LDAPObject` to a different class.)

```
class ldap.ldapobject.SimpleLDAPObject (uri, trace_level=0, trace_file=None,
                                         trace_stack_limit=5, bytes_mode=None,
                                         bytes_strictness=None, fileno=None)
```

This basic class wraps all methods of the underlying C API object.

The arguments are same as for the `initialize()` function.

```
class ldap.ldapobject.ReconnectLDAPObject (uri, trace_level=0, trace_file=None,
                                             trace_stack_limit=5, bytes_mode=None,
                                             bytes_strictness=None, retry_max=1,
                                             retry_delay=60.0, fileno=None)
```

`SimpleLDAPObject` subclass whose synchronous request methods automatically reconnect and re-try in case of server failure (`ldap.SERVER_DOWN`).

The first arguments are same as for the `initialize()` function. For automatic reconnects it has additional arguments:

- `retry_max`: specifies the number of reconnect attempts before re-raising the `ldap.SERVER_DOWN` exception.
- `retry_delay`: specifies the time in seconds between reconnect attempts.

This class also implements the pickle protocol.

Arguments for LDAPv3 controls

The `ldap.controls` module can be used for constructing and decoding LDAPv3 controls. These arguments are available in the methods with names ending in `_ext` or `_ext_s`:

`serverctrls` is a list of `ldap.controls.LDAPControl` instances sent to the server along with the LDAP request (see module `ldap.controls`). These are controls which alter the behaviour of the server when processing the request if the control is supported by the server. The effect of controls might differ depending on the type of LDAP request or controls might not be applicable with certain LDAP requests at all.

`clientctrls` is a list of `ldap.controls.LDAPControl` instances passed to the client API and alter the behaviour of the client when processing the request.

Sending LDAP requests

Most methods on LDAP objects initiate an asynchronous request to the LDAP server and return a message id that can be used later to retrieve the result with `result()`.

Methods with names ending in `_s` are the synchronous form and wait for and return with the server's result, or with `None` if no data is expected.

LDAPObject instances have the following methods:

LDAPObject.**abandon** (*msgid*) → None

LDAPObject.**abandon_ext** (*msgid*[, *serverctrls=None*[, *clientctrls=None*]]) → None

Abandons an LDAP operation in progress without waiting for a LDAP response. The `msgid` argument should be the message ID of an outstanding LDAP operation as returned by the asynchronous methods `search()`, `modify()`, etc. The caller can expect that the result of an abandoned operation will not be returned from a future call to `result()`.

`serverctrls` and `clientctrls` like described in section *Arguments for LDAPv3 controls*.

LDAPObject.**add** (*dn*, *modlist*) → int

LDAPObject.**add_s** (*dn*, *modlist*) → None

`LDAPObject.add_ext(dn, modlist[, serverctrls=None[, clientctrls=None]])` → int

`LDAPObject.add_ext_s(dn, modlist[, serverctrls=None[, clientctrls=None]])` → tuple

Performs an LDAP add operation. The *dn* argument is the distinguished name (DN) of the entry to add, and *modlist* is a list of attributes to be added. The modlist is similar the one passed to `modify()`, except that the operation integer is omitted from the tuples in modlist. You might want to look into sub-module `refmod-ule{ldap.modlist}` for generating the modlist.

The asynchronous methods `add()` and `add_ext()` return the message ID of the initiated request.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The *dn* argument, and *mod_type* (second item) of *modlist* are text strings; see *Bytes/text management*.

`LDAPObject.bind(who, cred, method)` → int

`LDAPObject.bind_s(who, cred, method)` → None

`LDAPObject.cancel(cancelid[, serverctrls=None[, clientctrls=None]])` → None

Send cancels extended operation for an LDAP operation specified by *cancelid*. The *cancelid* should be the message id of an outstanding LDAP operation as returned by the asynchronous methods `search()`, `modify()` etc. The caller can expect that the result of an abandoned operation will not be returned from a future call to `result()`. In opposite to `abandon()` this extended operation gets an result from the server and thus should be preferred if the server supports it.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

RFC 3909 - Lightweight Directory Access Protocol (LDAP): Cancel Operation

`LDAPObject.compare(dn, attr, value)` → int

`LDAPObject.compare_s(dn, attr, value)` → bool

`LDAPObject.compare_ext(dn, attr, value[, serverctrls=None[, clientctrls=None]])` → int

`LDAPObject.compare_ext_s(dn, attr, value[, serverctrls=None[, clientctrls=None]])` → bool

Perform an LDAP comparison between the attribute named *attr* of entry *dn*, and the value *value*. The synchronous forms returns `True` or `False`. The asynchronous forms returns the message ID of the initiated request, and the result of the asynchronous compare can be obtained using `result()`. The operation can fail with an exception, e.g. `ldap.NO_SUCH_OBJECT` when *dn* does not exist or `ldap.UNDEFINED_TYPE` for an invalid attribute.

Note that the asynchronous technique yields the answer by raising the exception objects `ldap.COMPARE_TRUE` or `ldap.COMPARE_FALSE`.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The *dn* and *attr* arguments are text strings; see *Bytes/text management*.

`LDAPObject.delete(dn)` → int

`LDAPObject.delete_s(dn)` → None

`LDAPObject.delete_ext(dn[, serverctrls=None[, clientctrls=None]])` → int

`LDAPObject.delete_ext_s(dn[, serverctrls=None[, clientctrls=None]])` → tuple

Performs an LDAP delete operation on *dn*. The asynchronous form returns the message id of the initiated request, and the result can be obtained from a subsequent call to `result()`.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The *dn* argument is text string; see *Bytes/text management*.

`LDAPObject.extop(extreq[,serverctrls=None[,clientctrls=None]])` → int

LDAPObject.**extop_s** (*extreq*, *serverctrls=None*, *clientctrls=None*, *extop_resp_class=None*)]]) -> (*respoid*, *respvalue*)

Performs an LDAP extended operation. The asynchronous form returns the message id of the initiated request, and the result can be obtained from a subsequent call to `extop_result()`.

The *extreq* is an instance of class `ldap.extop.ExtendedRequest` containing the parameters for the extended operation request.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

If argument *extop_resp_class* is set to a sub-class of `ldap.extop.ExtendedResponse` this class is used to return an object of this class instead of a raw BER value in *respvalue*.

LDAPObject.**extop_result** (*self*, *msgid=ldap.RES_ANY*, *all=1*, *timeout=None*) -> (*respoid*, *respvalue*)
Wrapper method around `result4()` just for retrieving the result of an extended operation sent before.

LDAPObject.**modify** (*dn*, *modlist*) -> int

LDAPObject.**modify_s** (*dn*, *modlist*) -> None

LDAPObject.**modify_ext** (*dn*, *modlist* [, *serverctrls=None* [, *clientctrls=None*]]) -> int

LDAPObject.**modify_ext_s** (*dn*, *modlist* [, *serverctrls=None* [, *clientctrls=None*]]) -> tuple

Performs an LDAP modify operation on an entry's attributes. The *dn* argument is the distinguished name (DN) of the entry to modify, and *modlist* is a list of modifications to make to that entry.

Each element in the list *modlist* should be a tuple of the form (*mod_op*, *mod_type*, *mod_vals*), where *mod_op* indicates the operation (one of `ldap.MOD_ADD`, `ldap.MOD_DELETE`, or `ldap.MOD_REPLACE`), *mod_type* is a string indicating the attribute type name, and *mod_vals* is either a string value or a list of string values to add, delete or replace respectively. For the delete operation, *mod_vals* may be `None` indicating that all attributes are to be deleted.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The asynchronous methods `modify()` and `modify_ext()` return the message ID of the initiated request.

You might want to look into sub-module `ldap.modlist` for generating *modlist*.

The *dn* argument, and *mod_type* (second item) of *modlist* are text strings; see *Bytes/text management*.

LDAPObject.**modrdn** (*dn*, *newrdn* [, *delold=1*]) -> int

LDAPObject.**modrdn_s** (*dn*, *newrdn* [, *delold=1*]) -> None

Perform a `modify RDN` operation, (i.e. a renaming operation). These routines take *dn* (the DN of the entry whose RDN is to be changed, and *newrdn*, the new RDN to give to the entry. The optional parameter *delold* is used to specify whether the old RDN should be kept as an attribute of the entry or not. The asynchronous version returns the initiated message id.

This operation is emulated by `rename()` and `rename_s()` methods since the `modrdn2*` routines in the C library are deprecated.

The *dn* and *newrdn* arguments are text strings; see *Bytes/text management*.

LDAPObject.**passwd** (*user*, *oldpw*, *newpw* [, *serverctrls=None* [, *clientctrls=None*]]) -> int

LDAPObject.**passwd_s** (*user*, *oldpw*, *newpw* [, *serverctrls=None* [, *clientctrls=None*] [, *extract_newpw=False*]]) -> (*respoid*, *respvalue*)

Perform a LDAP Password Modify Extended Operation operation on the entry specified by *user*. The old password in *oldpw* is replaced with the new password in *newpw* by a LDAP server supporting this operation.

If *oldpw* is not `None` it has to match the old password of the specified *user* which is sometimes used when a user changes his own password.

respoid is always `None`. *respvalue* is also `None` unless *newpw* was `None`. This requests that the server generate a new random password. If *extract_newpw* is `True`, this password is a bytes object available through `respvalue.genPasswd`, otherwise *respvalue* is the raw ASN.1 response (this is deprecated and only for backwards compatibility).

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The asynchronous version returns the initiated message id.

The *user*, *oldpw* and *newpw* arguments are text strings; see *Bytes/text management*.

See also:

RFC 3062 - LDAP Password Modify Extended Operation `ldap.extop.passwd`

`LDAPObject.rename(dn, newrdn[, newsuperior=None[, delold=1[, serverctrls=None[, clientctrls=None]]]])` → int

`LDAPObject.rename_s(dn, newrdn[, newsuperior=None[, delold=1[, serverctrls=None[, clientctrls=None]]]])` → None

Perform a Rename operation, (i.e. a renaming operation). These routines take *dn* (the DN of the entry whose RDN is to be changed, and *newrdn*, the new RDN to give to the entry. The optional parameter *newsuperior* is used to specify a new parent DN for moving an entry in the tree (not all LDAP servers support this). The optional parameter *delold* is used to specify whether the old RDN should be kept as an attribute of the entry or not.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The *dn* and *newrdn* arguments are text strings; see *Bytes/text management*.

`LDAPObject.result([msgid=RES_ANY[, all=1[, timeout=None]])` → 2-tuple

This method is used to wait for and return the result of an operation previously initiated by one of the LDAP asynchronous operations (e.g. `search()`, `modify()`, etc.)

The *msgid* parameter is the integer identifier returned by that method. The identifier is guaranteed to be unique across an LDAP session, and tells the `result()` method to request the result of that specific operation.

If a result is desired from any one of the in-progress operations, *msgid* should be specified as the constant `RES_ANY` and the method `result2()` should be used instead.

The *all* parameter only has meaning for `search()` responses and is used to select whether a single entry of the search response should be returned, or to wait for all the results of the search before returning.

A search response is made up of zero or more search entries followed by a search result. If *all* is 0, search entries will be returned one at a time as they come in, via separate calls to `result()`. If *all* is 1, the search response will be returned in its entirety, i.e. after all entries and the final search result have been received.

For *all* set to 0, result tuples trickle in (with the same message id), and with the result types `RES_SEARCH_ENTRY` and `RES_SEARCH_REFERENCE`, until the final result which has a result type of `RES_SEARCH_RESULT` and a (usually) empty data field. When *all* is set to 1, only one result is returned, with a result type of `RES_SEARCH_RESULT`, and all the result tuples listed in the data field.

The *timeout* parameter is a limit on the number of seconds that the method will wait for a response from the server. If *timeout* is negative (which is the default), the method will wait indefinitely for a response. The timeout can be expressed as a floating-point value, and a value of 0 effects a poll. If a timeout does occur, a `ldap.TIMEOUT` exception is raised, unless polling, in which case `(None, None)` is returned.

The `result()` method returns a tuple of the form `(result-type, result-data)`. The first element, *result-type* is a string, being one of these module constants: `RES_BIND`, `RES_SEARCH_ENTRY`, `RES_SEARCH_REFERENCE`, `RES_SEARCH_RESULT`, `RES_MODIFY`, `RES_ADD`, `RES_DELETE`, `RES_MODRDN`, or `RES_COMPARE`.

If *all* is 0, one response at a time is returned on each call to `result()`, with termination indicated by `result-data` being an empty list.

See `search()` for a description of the search result's `result-data`, otherwise the `result-data` is normally meaningless.

`LDAPObject.result2(msgid=RES_ANY[, all=1[, timeout=None]])` → 3-tuple

This method behaves almost exactly like `result()`. But it returns a 3-tuple also containing the message id of the outstanding LDAP operation a particular result message belongs to. This is especially handy if one needs to dispatch results obtained with `msgid=RES_ANY` to several consumer threads which invoked a particular LDAP operation.

`LDAPObject.result3(msgid=RES_ANY[, all=1[, timeout=None]])` → 4-tuple

This method behaves almost exactly like `result2()`. But it returns an extra item in the tuple, the decoded server controls.

`LDAPObject.result4(msgid=RES_ANY[, all=1[, timeout=None[, add_ctrls=0[, add_intermediates=0[, add_extop=0[, resp_ctrl_classes=None]]]]]])`
→ 6-tuple

This method behaves almost exactly like `result3()`. But it returns an extra items in the tuple, the decoded results of an extended response.

The additional arguments are:

`add_ctrls` (integer flag) specifies whether response controls are returned.

`add_intermediates` (integer flag) specifies whether response controls of intermediate search results are returned.

`add_extop` (integer flag) specifies whether the response of an extended operation is returned. If using extended operations you should consider using the method `extop_result()` or `extop_s()` instead.

`resp_ctrl_classes` is a dictionary mapping the OID of a response controls to a `ldap.controls.ResponseControl` class of response controls known by the application. So the response control value will be automatically decoded. If None the global dictionary `ldap.controls.KNOWN_RESPONSE_CONTROLS` is used instead.

`LDAPObject.sasl_interactive_bind_s(who, auth[, serverctrls=None[, clientctrls=None[, sasl_flags=ldap.SASL_QUIET]])` → None

This call is used to bind to the directory with a SASL bind request.

`auth` is an `ldap.sasl.sasl()` instance.

`serverctrls` and `clientctrls` like described in section *Arguments for LDAPv3 controls*.

`LDAPObject.sasl_non_interactive_bind_s(sasl_mech[, serverctrls=None[, clientctrls=None[, sasl_flags=ldap.SASL_QUIET[, authz_id="]]]])`
→ None

This call is used to bind to the directory with a SASL bind request with non-interactive SASL mechanism defined with argument `sasl_mech` and internally calls `sasl_interactive_bind_s()`.

`serverctrls` and `clientctrls` like described in section *Arguments for LDAPv3 controls*.

`LDAPObject.sasl_external_bind_s([serverctrls=None[, clientctrls=None[, sasl_flags=ldap.SASL_QUIET[, authz_id="]]]])` → None

This call is used to bind to the directory with a SASL bind request with mechanism EXTERNAL and internally calls `sasl_non_interactive_bind_s()`.

`serverctrls` and `clientctrls` like described in section *Arguments for LDAPv3 controls*.

`LDAPObject.sasl_gssapi_bind_s([serverctrls=None[, clientctrls=None[, sasl_flags=ldap.SASL_QUIET[, authz_id="]]]])` → None

This call is used to bind to the directory with a SASL bind request with mechanism GSSAPI and internally calls `sasl_non_interactive_bind_s()`.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

```
LDAPObject.simple_bind([who=None[, cred=None[, serverctrls=None[, clientctrls=None ]]]]) → int
```

```
LDAPObject.simple_bind_s([who=None[, cred=None[, serverctrls=None[, clientctrls=None ]]]]) → None
```

After an LDAP object is created, and before any other operations can be attempted over the connection, a bind operation must be performed.

This method attempts to bind with the LDAP server using either simple authentication, or Kerberos (if available). The first and most general method, *bind()*, takes a third parameter, *method* which can currently solely be AUTH_SIMPLE.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The *who* and *cred* arguments are text strings; see *Bytes/text management*.

Changed in version 3.0: *simple_bind()* and *simple_bind_s()* now accept None for *who* and *cred*, too.

```
LDAPObject.search(base, scope[, filterstr='(objectClass=*)'[, attrlist=None[, attrsonly=0 ]]]) → int
```

```
LDAPObject.search_s(base, scope[, filterstr='(objectClass=*)'[, attrlist=None[, attrsonly=0 ]]]) → list|None
```

```
LDAPObject.search_st(base, scope[, filterstr='(objectClass=*)'[, attrlist=None[, attrsonly=0[, timeout=-1 ]]]]) → list|None
```

```
LDAPObject.search_ext(base, scope[, filterstr='(objectClass=*)'[, attrlist=None[, attrsonly=0[, serverctrls=None[, clientctrls=None[, timeout=-1[, sizelimit=0 ]]]]]]) → int
```

```
LDAPObject.search_ext_s(base, scope[, filterstr='(objectClass=*)'[, attrlist=None[, attrsonly=0[, serverctrls=None[, clientctrls=None[, timeout=-1[, sizelimit=0 ]]]]]]) → list|None
```

Perform an LDAP search operation, with *base* as the DN of the entry at which to start the search, *scope* being one of SCOPE_BASE (to search the object itself), SCOPE_ONELEVEL (to search the object's immediate children), or SCOPE_SUBTREE (to search the object and all its descendants).

The *filterstr* argument is a string representation of the filter to apply in the search.

See also:

RFC 4515 - Lightweight Directory Access Protocol (LDAP): String Representation of Search Filters.

Each result tuple is of the form (*dn*, *attrs*), where *dn* is a string containing the DN (distinguished name) of the entry, and *attrs* is a dictionary containing the attributes associated with the entry. The keys of *attrs* are strings, and the associated values are lists of strings.

The DN in *dn* is automatically extracted using the underlying libldap function `ldap_get_dn()`, which may raise an exception if the DN is malformed.

If *attrsonly* is non-zero, the values of *attrs* will be meaningless (they are not transmitted in the result).

The retrieved attributes can be limited with the *attrlist* parameter. If *attrlist* is None, all the attributes of each entry are returned.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

The synchronous form with timeout, *search_st()* or *search_ext_s()*, will block for at most *timeout* seconds (or indefinitely if *timeout* is negative). A `ldap.TIMEOUT` exception is raised if no result is received within the specified time.

The amount of search results retrieved can be limited with the *sizelimit* parameter when using `search_ext()` or `search_ext_s()` (client-side search limit). If non-zero not more than *sizelimit* results are returned by the server.

The *base* and *filterstr* arguments, and *attrlist* contents, are text strings; see *Bytes/text management*.

Changed in version 3.0: `filterstr=None` is equivalent to `filterstr='(objectClass=*)'`.

`LDAPObject.start_tls_s()` → None

Negotiate TLS with server. The `version` attribute must have been set to `VERSION3` (which it is by default) before calling this method. If TLS could not be started an exception will be raised.

See also:

RFC 2830 - Lightweight Directory Access Protocol (v3): Extension for Transport Layer Security

`LDAPObject.unbind()` → int

`LDAPObject.unbind_s()` → None

`LDAPObject.unbind_ext([serverctrls=None[, clientctrls=None]])` → int

`LDAPObject.unbind_ext_s([serverctrls=None[, clientctrls=None]])` → None

This call is used to unbind from the directory, terminate the current association, and free resources. Once called, the connection to the LDAP server is closed and the LDAP object is marked invalid. Further invocation of methods on the object will yield exceptions.

serverctrls and *clientctrls* like described in section *Arguments for LDAPv3 controls*.

These methods are all synchronous in nature.

`LDAPObject.whoami_s()` → string

This synchronous method implements the LDAP “Who Am I?” extended operation.

It is useful for finding out to find out which identity is assumed by the LDAP server after a SASL bind.

See also:

RFC 4532 - Lightweight Directory Access Protocol (LDAP) “Who am I?” Operation

Connection-specific LDAP options

`LDAPObject.get_option(option)` → int/string

This method returns the value of the LDAPObject option specified by *option*.

`LDAPObject.set_option(option, invalue)` → None

This method sets the value of the LDAPObject option specified by *option* to *invalue*.

Object attributes

If the underlying library provides enough information, each LDAP object will also have the following attributes. These attributes are mutable unless described as read-only.

`LDAPObject.deref` → int

Controls whether aliases are automatically dereferenced. This must be one of `DEREF_NEVER`, `DEREF_SEARCHING`, `DEREF_FINDING` or `DEREF_ALWAYS`. This option is mapped to option constant `OPT_DEREF` and used in the underlying OpenLDAP client lib.

LDAPObject.network_timeout -> int

Limit on waiting for a network response, in seconds. Defaults to `NO_LIMIT`. This option is mapped to option constant `OPT_NETWORK_TIMEOUT` and used in the underlying OpenLDAP client lib.

Changed in version 3.0.0: A timeout of `-1` or `None` resets timeout to infinity.

LDAPObject.protocol_version -> int

Version of LDAP in use (either `VERSION2` for LDAPv2 or `VERSION3` for LDAPv3). This option is mapped to option constant `OPT_PROTOCOL_VERSION` and used in the underlying OpenLDAP client lib.

Note: It is highly recommended to set the protocol version after establishing a LDAP connection with `ldap.initialize()` and before submitting the first request.

LDAPObject.sizelimit -> int

Limit on size of message to receive from server. Defaults to `NO_LIMIT`. This option is mapped to option constant `OPT_SIZELIMIT` and used in the underlying OpenLDAP client lib. Its use is deprecated in favour of `sizelimit` parameter when using `search_ext()`.

LDAPObject.timelimit -> int

Limit on waiting for any response, in seconds. Defaults to `NO_LIMIT`. This option is mapped to option constant `OPT_TIMELIMIT` and used in the underlying OpenLDAP client lib. Its use is deprecated in favour of using `timeout`.

LDAPObject.timeout -> int

Limit on waiting for any response, in seconds. Defaults to `NO_LIMIT`. This option is used in the wrapper module.

Example

The following example demonstrates how to open a connection to an LDAP server using the `ldap` module and invoke a synchronous subtree search.

```
>>> import ldap
>>> l = ldap.initialize('ldap://localhost:1390')
>>> l.search_s('ou=Testing,dc=stroeder,dc=de', ldap.SCOPE_SUBTREE, '(cn=fred*)', ['cn',
↳ 'mail'])
[(('cn=Fred Feuerstein,ou=Testing,dc=stroeder,dc=de', {'cn': ['Fred Feuerstein']})]
>>> r = l.search_s('ou=Testing,dc=stroeder,dc=de', ldap.SCOPE_SUBTREE, '(objectClass=*)
↳ ', ['cn', 'mail'])
>>> for dn,entry in r:
>>>     print('Processing', repr(dn))
>>>     handle_ldap_entry(entry)
```

5.3.2 ldap.asyncsearch Stream-processing of large search results

With newer Python versions one might want to consider using `ldap.resiter` instead.

Changed in version 3.0: In Python 3.7 `async` is a reserved keyword. The module `ldap.async` has been renamed to `ldap.asyncsearch`. The old name `ldap.async` is still available for backwards compatibility.

Deprecated since version 3.0: The old name `ldap.async` is deprecated, but will not be removed until Python 3.6 reaches end-of-life.

Classes

class ldap.asyncsearch.**AsyncSearchHandler** (*l*)

Class for stream-processing LDAP search results

Arguments:

l LDAPObject instance

afterFirstResult ()

Do anything you want right after successfully receiving but before processing first result

postProcessing ()

Do anything you want after receiving and processing all results

preProcessing ()

Do anything you want after starting search but before receiving and processing results

processResults (*ignoreResultsNumber=0, processResultsCount=0, timeout=-1*)

ignoreResultsNumber Don't process the first ignoreResultsNumber results.

processResultsCount If non-zero this parameters indicates the number of results processed is limited to processResultsCount.

timeout See parameter timeout of ldap.LDAPObject.result()

startSearch (*searchRoot, searchScope, filterStr, attrList=None, attrsOnly=0, timeout=-1, size-limit=0, serverctrls=None, clientctrls=None*)

searchRoot See parameter base of method LDAPObject.search()

searchScope See parameter scope of method LDAPObject.search()

filterStr See parameter filter of method LDAPObject.search()

attrList=None See parameter attrlist of method LDAPObject.search()

attrsOnly See parameter attrsonly of method LDAPObject.search()

timeout Maximum time the server shall use for search operation

sizelimit Maximum number of entries a server should return (request client-side limit)

serverctrls list of server-side LDAP controls

clientctrls list of client-side LDAP controls

class ldap.asyncsearch.**List** (*l*)

Class for collecting all search results.

This does not seem to make sense in the first place but think of retrieving exactly a certain portion of the available search results.

class ldap.asyncsearch.**Dict** (*l*)

Class for collecting all search results into a dictionary {dn:entry}

class ldap.asyncsearch.**IndexedDict** (*l, indexed_attrs=None*)

Class for collecting all search results into a dictionary {dn:entry} and maintain case-sensitive equality indexes to entries

class ldap.asyncsearch.**LDIFWriter** (*l, writer_obj, headerStr="", footerStr=""*)

Class for writing a stream LDAP search results to a LDIF file

Arguments:

l LDAPObject instance

writer_obj Either a file-like object or a `ldif.LDIFWriter` instance used for output

Examples

Using `ldap.asyncsearch.List`

This example demonstrates how to use class `ldap.asyncsearch.List` for retrieving partial search results even though the exception `ldap.SIZELIMIT_EXCEEDED` was raised because a server side limit was hit.

```
import sys, ldap, ldap.asyncsearch

s = ldap.asyncsearch.List(
    ldap.initialize('ldap://localhost'),
)

s.startSearch(
    'dc=stroeder,dc=com',
    ldap.SCOPE_SUBTREE,
    '(objectClass=*)',
)

try:
    partial = s.processResults()
except ldap.SIZELIMIT_EXCEEDED:
    sys.stderr.write('Warning: Server-side size limit exceeded.\n')
else:
    if partial:
        sys.stderr.write('Warning: Only partial results received.\n')

sys.stdout.write(
    '%d results received.\n' % (
        len(s.allResults)
    )
)
```

Using `ldap.asyncsearch.LDIFWriter`

This example demonstrates how to use class `ldap.asyncsearch.LDIFWriter` for writing search results as LDIF to stdout.

```
import sys, ldap, ldap.asyncsearch

s = ldap.asyncsearch.LDIFWriter(
    ldap.initialize('ldap://localhost:1390'),
    sys.stdout
)

s.startSearch(
    'dc=stroeder,dc=com',
    ldap.SCOPE_SUBTREE,
    '(objectClass=*)',
)

try:
    partial = s.processResults()
```

(continues on next page)

(continued from previous page)

```

except ldap.SIZELIMIT_EXCEEDED:
    sys.stderr.write('Warning: Server-side size limit exceeded.\n')
else:
    if partial:
        sys.stderr.write('Warning: Only partial results received.\n')

sys.stderr.write(
    '%d results received.\n' % (
        s.endResultBreak-s.beginResultsDropped
    )
)

```

5.3.3 ldap.controls High-level access to LDAPv3 extended controls

Variables

`ldap.controls.KNOWN_RESPONSE_CONTROLS`

Dictionary mapping the OIDs of known response controls to the accompanying *ResponseControl* classes. This is used by *DecodeControlTuples()* to automatically decode control values. Calling application can also register their custom *ResponseControl* classes in this dictionary possibly overriding pre-registered classes.

Classes

This module defines the following classes:

class `ldap.controls.RequestControl` (*controlType=None, criticality=False, encodedControlValue=None*)

Base class for all request controls

controlType OID as string of the LDAPv3 extended request control

criticality sets the criticality of the control (boolean)

encodedControlValue control value of the LDAPv3 extended request control (here it is the BER-encoded ASN.1 control value)

encodeControlValue()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.ResponseControl` (*controlType=None, criticality=False*)

Base class for all response controls

controlType OID as string of the LDAPv3 extended response control

criticality sets the criticality of the received control (boolean)

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

class `ldap.controls.LDAPControl` (*controlType=None, criticality=False, controlValue=None, encodedControlValue=None*)

Base class for combined request/response controls mainly for backward-compatibility to python-ldap 2.3.x

Functions

This module defines the following functions:

`ldap.controls.RequestControlTuples` (*ldapControls*)

Return list of readily encoded 3-tuples which can be directly passed to C module `_ldap`

ldapControls sequence-type of RequestControl objects

`ldap.controls.DecodeControlTuples` (*ldapControlTuples, knownLDAPControls=None*)

Returns list of readily decoded ResponseControl objects

ldapControlTuples Sequence-type of 3-tuples returned by `_ldap.result4()` containing the encoded ASN.1 control values of response controls.

knownLDAPControls Dictionary mapping extended control's OID to ResponseControl class of response controls known by the application. If `None` `ldap.controls.KNOWN_RESPONSE_CONTROLS` is used here.

Sub-modules

Various sub-modules implement specific LDAPv3 extended controls. The classes therein are derived from the base-classes `ldap.controls.RequestControl`, `ldap.controls.ResponseControl` or `ldap.controls.LDAPControl`.

Some of them require `pyasn1` and `pyasn1_modules` to be installed:

Usually the names of the method arguments and the class attributes match the ASN.1 identifiers used in the specification. So looking at the referenced RFC or Internet-Draft is very helpful to understand the API.

`ldap.controls.simple` Very simple controls

class `ldap.controls.simple.ValueLessRequestControl` (*controlType=None, criticality=False*)

Base class for controls without a controlValue. The presence of the control in a LDAPv3 request changes the server's behaviour when processing the request simply based on the controlType.

controlType OID of the request control

criticality criticality request control

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.simple.OctetStringInteger` (*controlType=None, criticality=False, integerValue=None*)

Base class with controlValue being unsigned integer values

integerValue Integer to be sent as OctetString

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.simple.BooleanControl` (*controlType=None, criticality=False, booleanValue=False*)

Base class for simple request controls with boolean control value.

Constructor argument and class attribute:

booleanValue Boolean (True/False or 1/0) which is the boolean controlValue.

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.simple.ManageDSAITControl` (*criticality=False*)

Manage DSA IT Control

See also:

[RFC 3296](#) - Named Subordinate References in Lightweight Directory Access Protocol (LDAP) Directories

class `ldap.controls.simple.RelaxRulesControl` (*criticality=False*)

Relax Rules Control

See also:

[draft-zeilenga-ldap-relax](#)

class `ldap.controls.simple.ProxyAuthzControl` (*criticality, authzId*)

Proxy Authorization Control

authzId string containing the authorization ID indicating the identity on behalf which the server should process the request

See also:

[RFC 4370](#) - Lightweight Directory Access Protocol (LDAP): Proxied Authorization Control

class `ldap.controls.simple.AuthorizationIdentityRequestControl` (*criticality*)

Authorization Identity Request and Response Controls

See also:

[RFC 3829](#) - Lightweight Directory Access Protocol (LDAP): Authorization Identity Request and Response Controls

class `ldap.controls.simple.AuthorizationIdentityResponseControl` (*controlType=None, criticality=False*)

Authorization Identity Request and Response Controls

Class attributes:

authzId decoded authorization identity

See also:

[RFC 3829](#) - Lightweight Directory Access Protocol (LDAP): Authorization Identity Request and Response Controls

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

class `ldap.controls.simple.GetEffectiveRightsControl` (*criticality, authzId=None*)

Get Effective Rights Control

`ldap.controls.libldap` Various controls implemented in OpenLDAP libs

This module wraps C functions in OpenLDAP client libs which implement various request and response controls into Python classes.

class `ldap.controls.libldap.AssertionControl` (*criticality=True*, *filter-str='(objectClass=*)'*)

LDAP Assertion control, as defined in RFC 4528

filterstr LDAP filter string specifying which assertions have to match so that the server processes the operation

See also:

[RFC 4528](#) - Lightweight Directory Access Protocol (LDAP) Assertion Control

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.libldap.MatchedValuesControl` (*criticality=False*, *filter-str='(objectClass=*)'*)

LDAP Matched Values control, as defined in RFC 3876

filterstr LDAP filter string specifying which attribute values should be returned

See also:

[RFC 3876](#) - Returning Matched Values with the Lightweight Directory Access Protocol version 3 (LDAPv3)

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.libldap.SimplePagedResultsControl` (*criticality=False*, *size=None*, *cookie=None*)

LDAP Control Extension for Simple Paged Results Manipulation

size Page size requested (number of entries to be returned)

cookie Cookie string received with last page

See also:

[RFC 2696](#) - LDAP Control Extension for Simple Paged Results Manipulation

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

`ldap.controls.psearch` LDAP Persistent Search

This module implements request and response controls for LDAP persistent search.

See also:

[draft-ietf-ldapext-psearch](#)

```
class ldap.controls.psearch.PersistentSearchControl (criticality=True,  
changeTypes=None,  
changesOnly=False, re-  
turnECs=True)
```

Implements the request control for persistent search.

changeTypes List of strings specifying the types of changes returned by the server. Setting to None requests all changes.

changesOnly Boolean which indicates whether only changes are returned by the server.

returnECs Boolean which indicates whether the server should return an Entry Change Notification response control

```
class PersistentSearchControlValue (**kwargs)
```

```
encodeControlValue ()
```

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

```
class ldap.controls.psearch.EntryChangeNotificationControl (controlType=None,  
criticality=False)
```

Implements the response control for persistent search.

Class attributes with values extracted from the response control:

changeType String indicating the type of change causing this result to be returned by the server

previousDN Old DN of the entry in case of a modrdn change

changeNumber A change serial number returned by the server (optional).

```
decodeControlValue (encodedControlValue)
```

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

`ldap.controls.sessiontrack` Session tracking control

See also:

[draft-wahl-ldap-session](#)

```
class ldap.controls.sessiontrack.SessionTrackingControl (sessionSourceIp, session-  
SourceName, formatOID,  
sessionTrackingIdentifier)
```

Class for Session Tracking Control

Because criticality MUST be false for this control it cannot be set from the application.

sessionSourceIp IP address of the request source as string

sessionSourceName Name of the request source as string

formatOID OID as string specifying the format

sessionTrackingIdentifier String containing a specific tracking ID

```
class SessionIdentifierControlValue (**kwargs)
```

```
encodeControlValue ()
```

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

`ldap.controls.readentry` Read entry control

See also:

[RFC 4527](#) - Lightweight Directory Access Protocol (LDAP): Read Entry Controls

Changed in version 4.0: The attribute values of the entry now consists of *bytes* instead of ISO8859-1 decoded *str*.

class `ldap.controls.readentry.ReadEntryControl` (*criticality=False, attrList=None*)

Base class for read entry control described in RFC 4527

attrList list of attribute type names requested

Class attributes with values extracted from the response control:

dn string holding the distinguished name of the LDAP entry

entry dictionary holding the LDAP entry

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

encodeControlValue ()

sets class attribute `encodedControlValue` to the BER-encoded ASN.1 control value composed by class attributes set before

class `ldap.controls.readentry.PreReadControl` (*criticality=False, attrList=None*)

Class for pre-read control described in RFC 4527

attrList list of attribute type names requested

Class attributes with values extracted from the response control:

dn string holding the distinguished name of the LDAP entry before the operation was done by the server

entry dictionary holding the LDAP entry before the operation was done by the server

class `ldap.controls.readentry.PostReadControl` (*criticality=False, attrList=None*)

Class for post-read control described in RFC 4527

attrList list of attribute type names requested

Class attributes with values extracted from the response control:

dn string holding the distinguished name of the LDAP entry after the operation was done by the server

entry dictionary holding the LDAP entry after the operation was done by the server

`ldap.controls.ppolicy` Password Policy Control

See also:

[draft-behera-ldap-password-policy](#)

class `ldap.controls.ppolicy.PasswordPolicyControl` (*criticality=False*)

Indicates the errors and warnings about the password policy.

timeBeforeExpiration

The time before the password expires.

Type `int`

graceAuthNsRemaining

The number of grace authentications remaining.

Type int

error

The password and authentication errors.

Type int

decodeControlValue (*encodedControlValue*)

decodes the BER-encoded ASN.1 control value and sets the appropriate class attributes

5.3.4 ldap.dn LDAP Distinguished Name handling

See also:

For LDAPv3 DN syntax see:

RFC 4514 - Lightweight Directory Access Protocol (LDAP): String Representation of Distinguished Names

See also:

For deprecated LDAPv2 DN syntax (obsoleted by LDAPv3) see:

RFC 1779 - A String Representation of Distinguished Names

The `ldap.dn` module defines the following functions:

`ldap.dn.escape_dn_chars` (*s*) → string

This function escapes characters in string *s* which are special in LDAP distinguished names. You should use this function when building LDAP DN strings from arbitrary input.

`ldap.dn.str2dn` (*s*[, *flags=0*]) → list

This function takes *s* and breaks it up into its component parts down to AVA level. The optional parameter *flags* describes the DN format of *s* (see *DN format flags*). Note that hex-encoded non-ASCII chars are decoded to the raw bytes.

Internally this function is implemented by calling OpenLDAP C function `ldap_str2dn(3)`.

`ldap.dn.dn2str` (*dn*) → string

This function takes a decomposed DN in *dn* and returns a single string. It's the inverse to `str2dn()`. Special characters are escaped with the help of function `escape_dn_chars()`.

`ldap.dn.explode_dn` (*dn*[, *notypes=False*[, *flags=0*]]) → list

This function takes *dn* and breaks it up into its component parts. Each part is known as an RDN (Relative Distinguished Name). The optional *notypes* parameter is used to specify that only the RDN values be returned and not their types. The optional parameter *flags* describes the DN format of *s* (see *DN format flags*). This function is emulated by function `str2dn()` since the function `ldap_explode_dn()` in the C library is deprecated.

`ldap.dn.explode_rdn` (*rdn*[, *notypes=False*[, *flags=0*]]) → list

This function takes a (multi-valued) *rdn* and breaks it up into a list of characteristic attributes. The optional *notypes* parameter is used to specify that only the RDN values be returned and not their types. The optional *flags* parameter describes the DN format of *s* (see *DN format flags*). This function is emulated by function `str2dn()` since the function `ldap_explode_rdn()` in the C library is deprecated.

`ldap.dn.is_dn` (*dn*[, *flags=0*]) → boolean

This function checks whether *dn* is a valid LDAP distinguished name by passing it to function `str2dn()`.

Examples

Splitting a LDAPv3 DN to AVA level. Note that both examples have the same result but in the first example the non-ASCII chars are passed as is (byte buffer string) whereas in the second example the hex-encoded DN representation

are passed to the function.

```
>>> ldap.dn.str2dn('cn=Michael Str\xc3\xb6der,dc=example,dc=com', flags=ldap.DN_FORMAT_
↳LDAPV3)
[[('cn', 'Michael Str\xc3\xb6der', 4)], [('dc', 'example', 1)], [('dc', 'com', 1)]]
>>> ldap.dn.str2dn('cn=Michael Str\C3\B6der,dc=example,dc=com', flags=ldap.DN_FORMAT_
↳LDAPV3)
[[('cn', 'Michael Str\xc3\xb6der', 4)], [('dc', 'example', 1)], [('dc', 'com', 1)]]
```

Splitting a LDAPv2 DN into RDN parts:

```
>>> ldap.dn.explode_dn('cn=John Doe;dc=example;dc=com', flags=ldap.DN_FORMAT_LDAPV2)
['cn=John Doe', 'dc=example', 'dc=com']
```

Splitting a multi-valued RDN:

```
>>> ldap.dn.explode_rdn('cn=John Doe+mail=john.doe@example.com', flags=ldap.DN_FORMAT_
↳LDAPV2)
['cn=John Doe', 'mail=john.doe@example.com']
```

Splitting a LDAPv3 DN with a multi-valued RDN into its AVA parts:

```
>>> ldap.dn.str2dn('cn=John Doe+mail=john.doe@example.com,dc=example,dc=com')
[[('cn', 'John Doe', 1), ('mail', 'john.doe@example.com', 1)], [('dc', 'example', 1)],
↳ [('dc', 'com', 1)]]
```

5.3.5 ldap.extop High-level access to LDAPv3 extended operations

Classes

This module defines the following classes:

```
class ldap.extop.ExtendedRequest (requestName, requestValue)
    Generic base class for a LDAPv3 extended operation request

    requestName OID as string of the LDAPv3 extended operation request
    requestValue value of the LDAPv3 extended operation request (here it is the BER-encoded ASN.1 request
        value)

    encodedRequestValue ()
        returns the BER-encoded ASN.1 request value composed by class attributes set before

class ldap.extop.ExtendedResponse (responseName, encodedResponseValue)
    Generic base class for a LDAPv3 extended operation response

    requestName OID as string of the LDAPv3 extended operation response
    encodedResponseValue BER-encoded ASN.1 value of the LDAPv3 extended operation response

    decodeResponseValue (value)
        decodes the BER-encoded ASN.1 extended operation response value and sets the appropriate class at-
        tributes
```

ldap.extop.dds Classes for Dynamic Entries extended operations

This requires pyasn1 and pyasn1_modules to be installed.

See also:

RFC 2589 - Lightweight Directory Access Protocol (v3): Extensions for Dynamic Directory Services

```
class ldap.extop.dds.RefreshRequest (requestName=None, entryName=None, re-
questTtl=None)
```

```
class RefreshRequestValue (**kwargs)
```

```
encodedRequestValue ()
```

returns the BER-encoded ASN.1 request value composed by class attributes set before

```
class ldap.extop.dds.RefreshResponse (responseName, encodedResponseValue)
```

```
class RefreshResponseValue (**kwargs)
```

```
decodeResponseValue (value)
```

decodes the BER-encoded ASN.1 extended operation response value and sets the appropriate class attributes

5.3.6 ldap.filter LDAP filter handling

See also:

RFC 4515 - Lightweight Directory Access Protocol (LDAP): String Representation of Search Filters.

The `ldap.filter` module defines the following functions:

```
ldap.filter.escape_filter_chars (assertion_value[, escape_mode=0])
```

This function escapes characters in `assertion_value` which are special in LDAP filters. You should use this function when building LDAP filter strings from arbitrary input. `escape_mode` means: If 0 only special chars mentioned in RFC 4515 are escaped. If 1 all NON-ASCII chars are escaped. If 2 all chars are escaped.

```
ldap.filter.filter_format (filter_template, assertion_values)
```

This function applies `escape_filter_chars()` to each of the strings in list `assertion_values`. After that `filter_template` containing as many `%s` placeholders as count of assertion values is used to build the whole filter string.

5.3.7 ldap.modlist Generate modify lists

The `ldap.modlist` module defines the following functions:

```
ldap.modlist.addModlist (entry[, ignore_attr_types=[]]) → list
```

This function builds a list suitable for passing it directly as argument `modlist` to method `ldap.ldapobject.LDAPObject.add()` or its synchronous counterpart `ldap.ldapobject.LDAPObject.add_s()`.

`entry` is a dictionary like returned when receiving search results.

`ignore_attr_types` is a list of attribute type names which shall be ignored completely. Attributes of these types will not appear in the result at all.

```
ldap.modlist.modifyModlist (old_entry, new_entry[, ignore_attr_types=[], ignore_oldexistent=0[,
case_ignore_attr_types=None]]) → list
```

This function builds a list suitable for passing it directly as argument `modlist` to method `ldap.ldapobject.LDAPObject.modify()` or its synchronous counterpart `ldap.ldapobject.LDAPObject.modify_s()`.

Roughly when applying the resulting modify list to an entry holding the data *old_entry* it will be modified in such a way that the entry holds *new_entry* after the modify operation. It is handy in situations when it is impossible to track user changes to an entry's data or for synchronizing operations.

old_entry and *new_entry* are dictionaries like returned when receiving search results.

ignore_attr_types is a list of attribute type names which shall be ignored completely. These attribute types will not appear in the result at all.

If *ignore_oldexistent* is non-zero attribute type names which are in *old_entry* but are not found in *new_entry* at all are not deleted. This is handy for situations where your application sets attribute value to an empty string for deleting an attribute. In most cases leave zero.

If *case_ignore_attr_types* is a list of attribute type names for which the comparison will be conducted case-insensitive. It is useful in situations where a LDAP server normalizes values and one wants to avoid unnecessary changes (e.g. case of attribute type names in DNS).

Note: Replacing attribute values is always done with a `ldap.MOD_DELETE/ldap.MOD_ADD` pair instead of `ldap.MOD_REPLACE` to work-around potential issues with attributes for which no EQUALITY matching rule are defined in the server's subschema. This works correctly in most situations but rarely fails with some LDAP servers implementing (schema) checks on transient state entry during processing the modify operation.

5.3.8 `ldap.resiter` Generator for stream-processing of large search results

class `ldap.resiter.ResultProcessor`

This is a mix-in class to be used with class `ldap.LDAPObject` or derived classes which has these methods:

`ResultProcessor.allresults(msgid, timeout=-1, add_ctrls=0)`

Generator function which returns an iterator for processing all LDAP operation results of the given msgid like retrieved with `LDAPObject.result3()` -> 4-tuple

Examples

Using `ldap.resiter.ResultProcessor`

This example demonstrates how to use mix-in class `ldap.resiter.ResultProcessor` for retrieving results formerly requested with `ldap.LDAPObject.search()` and processing them in a for-loop.

```
import sys, ldap, ldap.resiter

class MyLDAPObject(ldap.LDAPObject, ldap.resiter.ResultProcessor):
    pass

l = MyLDAPObject('ldap://localhost')

# Asynchronous search method
msg_id = l.search('dc=stroeder,dc=com', ldap.SCOPE_SUBTREE, '(objectClass=*)')

for res_type, res_data, res_msgid, res_controls in l.allresults(msg_id):
    for dn, entry in res_data:
        # process dn and entry
        print(dn, entry['objectClass'])
```

5.3.9 ldap.schema Handling LDAPv3 schema

This module deals with schema information usually retrieved from a special subschema subentry provided by the server. It is closely modeled along the directory information model described in the following RFC with which you should make yourself familiar when trying to use this module:

See also:

RFC 4512 - Lightweight Directory Access Protocol (LDAP): Directory Information Models

ldap.schema.subentry Processing LDAPv3 subschema subentry

`ldap.schema.subentry.NOT_HUMAN_READABLE_LDAP_SYNTAXES`

Dictionary where the keys are the OIDs of LDAP syntaxes known to be not human-readable when displayed to a console without conversion and which cannot be decoded to a `types.UnicodeType`.

Functions

`ldap.schema.subentry.urlfetch(uri, trace_level=0)`

Fetches a parsed schema entry by uri.

If uri is a LDAP URL the LDAP server is queried directly. Otherwise uri is assumed to point to a LDIF file which is loaded with `urllib`.

Classes

class `ldap.schema.subentry.SubSchema(sub_schema_sub_entry, check_uniqueness=1)`

Arguments:

sub_schema_sub_entry Dictionary usually returned by LDAP search or the LDIF parser containing the sub schema sub entry

check_uniqueness Defines whether uniqueness of OIDs and NAME is checked.

0 no check

1 check but add schema description with work-around

2 check and raise exception if non-unique OID or NAME is found

Class attributes:

sed Dictionary holding the subschema information as pre-parsed `SchemaElement` objects (do not access directly!)

name2oid Dictionary holding the mapping from NAMES to OIDs (do not access directly!)

non_unique_oids List of OIDs used at least twice in the subschema

non_unique_names List of NAMES used at least twice in the subschema for the same schema element

attribute_types (`object_class_list, attr_type_filter=None, raise_keyerror=1, ignore_dit_content_rule=0`)

Returns a 2-tuple of all must and may attributes including all inherited attributes of superior object classes by walking up classes along the SUP attribute.

The attributes are stored in a `ldap.cidict.cidict` dictionary.

object_class_list list of strings specifying object class names or OIDs

attr_type_filter list of 2-tuples containing lists of class attributes which has to be matched

raise_keyerror All KeyError exceptions for non-existent schema elements are ignored

ignore_dit_content_rule A DIT content rule governing the structural object class is ignored

get_applicable_aux_classes (*nameoroid*)

Return a list of the applicable AUXILIARY object classes for a STRUCTURAL object class specified by 'nameoroid' if the object class is governed by a DIT content rule. If there's no DIT content rule all available AUXILIARY object classes are returned.

get_inheritedattr (*se_class, nameoroid, name*)

Get a possibly inherited attribute specified by name of a schema element specified by nameoroid. Returns None if class attribute is not set at all.

Raises KeyError if no schema element is found by nameoroid.

get_inheritedobj (*se_class, nameoroid, inherited=None*)

Get a schema element by name or OID with all class attributes set including inherited class attributes

get_obj (*se_class, nameoroid, default=None, raise_keyerror=0*)

Get a schema element by name or OID

get_structural_oc (*oc_list*)

Returns OID of structural object class in oc_list if any is present. Returns None else.

get_syntax (*nameoroid*)

Get the syntax of an attribute type specified by name or OID

getoid (*se_class, nameoroid, raise_keyerror=0*)

Get an OID by name or OID

ldap_entry ()

Returns a dictionary containing the sub schema sub entry

listall (*schema_element_class, schema_element_filters=None*)

Returns a list of OIDs of all available schema elements of a given schema element class.

tree (*schema_element_class, schema_element_filters=None*)

Returns a ldap.cidict.cidict dictionary representing the tree structure of the schema elements.

ldap.schema.models Schema elements

class ldap.schema.models.**Entry** (*schema, dn, entry*)

Schema-aware implementation of an LDAP entry class.

Mainly it holds the attributes in a string-keyed dictionary with the OID as key.

attribute_types (*attr_type_filter=None, raise_keyerror=1*)

Convenience wrapper around SubSchema.attribute_types() which passes object classes of this particular entry as argument to SubSchema.attribute_types()

items () → a set-like object providing a view on D's items

keys () → a set-like object providing a view on D's keys

update (*[E], **F*) → None. Update D from mapping/iterable E and F.

If E present and has a .keys() method, does: for k in E: D[k] = E[k] If E present and lacks .keys() method, does: for (k, v) in E: D[k] = v In either case, this is followed by: for k, v in F.items(): D[k] = v

class ldap.schema.models.**SchemaElement** (*schema_element_str=None*)

Base class for all schema element classes. Not used directly!

Arguments:

schema_element_str String which contains the schema element description to be parsed. (Bytestrings are decoded using UTF-8)

Class attributes:

schema_attribute LDAP attribute type containing a certain schema element description

token_defaults Dictionary internally used by the schema element parser containing the defaults for certain schema description key-words

class ldap.schema.models.**AttributeType** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an AttributeTypeDescription

Class attributes:

oid OID assigned to the attribute type (string)

names All NAMEs of the attribute type (tuple of strings)

desc Description text (DESC) of the attribute type (string, or None if missing)

obsolete Integer flag (0 or 1) indicating whether the attribute type is marked as OBSOLETE in the schema

single_value Integer flag (0 or 1) indicating whether the attribute must have only one value

syntax OID of the LDAP syntax assigned to the attribute type

no_user_mod Integer flag (0 or 1) indicating whether the attribute is modifiable by a client application

equality NAME or OID of the matching rule used for checking whether attribute values are equal (string, or None if missing)

substr NAME or OID of the matching rule used for checking whether an attribute value contains another value (string, or None if missing)

ordering NAME or OID of the matching rule used for checking whether attribute values are lesser-equal than (string, or None if missing)

usage USAGE of an attribute type: 0 = userApplications 1 = directoryOperation, 2 = distributedOperation, 3 = dSAOperation

sup NAMEs or OIDs of attribute types this attribute type is derived from (tuple of strings)

x_origin Value of the X-ORIGIN extension flag (tuple of strings).

Although it's not official, X-ORIGIN is used in several LDAP server implementations to indicate the source of the associated schema element

class ldap.schema.models.**ObjectClass** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an ObjectClassDescription

Class attributes:

oid OID assigned to the object class

names All NAMEs of the object class (tuple of strings)

desc Description text (DESC) of the object class (string, or None if missing)

obsolete Integer flag (0 or 1) indicating whether the object class is marked as OBSOLETE in the schema

must NAMEs or OIDs of all attributes an entry of the object class must have (tuple of strings)

may NAMES or OIDs of additional attributes an entry of the object class may have (tuple of strings)

kind Kind of an object class: 0 = STRUCTURAL, 1 = ABSTRACT, 2 = AUXILIARY

sup NAMES or OIDs of object classes this object class is derived from (tuple of strings)

x_origin Value of the X-ORIGIN extension flag (tuple of strings)

Although it's not official, X-ORIGIN is used in several LDAP server implementations to indicate the source of the associated schema element

class ldap.schema.models.**MatchingRule** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an MatchingRuleDescription

Class attributes:

oid OID assigned to the matching rule

names All NAMES of the matching rule (tuple of strings)

desc Description text (DESC) of the matching rule

obsolete Integer flag (0 or 1) indicating whether the matching rule is marked as OBSOLETE in the schema

syntax OID of the LDAP syntax this matching rule is usable with (string, or None if missing)

class ldap.schema.models.**MatchingRuleUse** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an MatchingRuleUseDescription

Class attributes:

oid OID of the accompanying matching rule

names All NAMES of the matching rule (tuple of strings)

desc Description text (DESC) of the matching rule (string, or None if missing)

obsolete Integer flag (0 or 1) indicating whether the matching rule is marked as OBSOLETE in the schema

applies NAMES or OIDs of attribute types for which this matching rule is used (tuple of strings)

class ldap.schema.models.**DITContentRule** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an DITContentRuleDescription

Class attributes:

oid OID of the accompanying structural object class

names All NAMES of the DIT content rule (tuple of strings)

desc Description text (DESC) of the DIT content rule (string, or None if missing)

obsolete Integer flag (0 or 1) indicating whether the DIT content rule is marked as OBSOLETE in the schema

aux NAMES or OIDs of all auxiliary object classes usable in an entry of the object class (tuple of strings)

must NAMES or OIDs of all attributes an entry of the object class must have, which may extend the list of required attributes of the object classes of an entry. (tuple of strings)

may NAMES or OIDs of additional attributes an entry of the object class may have. which may extend the list of optional attributes of the object classes of an entry. (tuple of strings)

nots NAMES or OIDs of attributes which may not be present in an entry of the object class. (tuple of strings)

class ldap.schema.models.**NameForm** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an NameFormDescription

Class attributes:

oid OID of the name form

names All NAMES of the name form (tuple of strings)

desc Description text (DESC) of the name form (string, or None if missing)

obsolete Integer flag (0 or 1) indicating whether the name form is marked as OBSOLETE in the schema

form NAMES or OIDs of associated name forms (tuple of strings)

oc NAME or OID of structural object classes this name form is usable with (string)

must NAMES or OIDs of all attributes an RDN must contain (tuple of strings)

may NAMES or OIDs of additional attributes an RDN may contain (tuple of strings)

class ldap.schema.models.**DITStructureRule** (*schema_element_str=None*)

Arguments:

schema_element_str String containing an DITStructureRuleDescription

Class attributes:

ruleid rule ID of the DIT structure rule (only locally unique)

names All NAMES of the DIT structure rule (tuple of strings)

desc Description text (DESC) of the DIT structure rule (string, or None if missing)

obsolete Integer flag (0 or 1) indicating whether the DIT content rule is marked as OBSOLETE in the schema

form NAMES or OIDs of associated name forms (tuple of strings)

sup NAMES or OIDs of allowed structural object classes of superior entries in the DIT (tuple of strings)

Examples for ldap.schema

```
import ldap.schema
```

5.3.10 ldap.syncrepl Implementation of a syncrepl consumer

See also:

RFC 4533 - Lightweight Directory Access Protocol (v3): Content Synchronization Operation

This requires pyasn1 and pyasn1_modules to be installed.

Classes

This module defines the following classes:

class ldap.syncrepl.**SyncreplConsumer**

SyncreplConsumer - LDAP syncrepl consumer object.

syncrepl_delete (*uuids*)

Called by `syncrepl_poll()` to delete entries. A list of UUIDs of the entries to be deleted is given in the `uuids` parameter.

syncrepl_entry (*dn, attrs, uuid*)

Called by `syncrepl_poll()` for any added or modified entries.

The provided `uuid` is used to identify the provided entry in any future modification (including `dn` modification), deletion, and presentation operations.

syncrepl_get_cookie ()

Called by `syncrepl_search()` to retrieve the cookie stored by `syncrepl_set_cookie()`

syncrepl_poll (*msgid=-1, timeout=None, all=0*)

polls for and processes responses to the `syncrepl_search()` operation. Returns `False` when operation finishes, `True` if it is in progress, or raises an exception on error.

If `timeout` is specified, raises `ldap.TIMEOUT` in the event of a timeout.

If `all` is set to a nonzero value, `poll()` will return only when finished or when an exception is raised.

syncrepl_present (*uuids, refreshDeletes=False*)

Called by `syncrepl_poll()` whenever entry UUIDs are presented to the client. `syncrepl_present()` is given a list of entry UUIDs (`uuids`) and a flag (`refreshDeletes`) which indicates whether the server explicitly deleted non-present entries during the refresh operation.

If called with a list of `uuids`, the `syncrepl_present()` implementation should record those `uuids` as present in the directory.

If called with `uuids` set to `None` and `refreshDeletes` set to `False`, `syncrepl_present()` should delete all non-present entries from the local mirror, and reset the list of recorded `uuids`.

If called with `uuids` set to `None` and `refreshDeletes` set to `True`, `syncrepl_present()` should reset the list of recorded `uuids`, without deleting any entries.

syncrepl_refreshdone ()

Called by `syncrepl_poll()` between refresh and persist phase.

It indicates that initial synchronization is done and persist phase follows.

syncrepl_search (*base, scope, mode='refreshOnly', cookie=None, **search_args*)

Starts `syncrepl` search operation.

`base`, `scope`, and `search_args` are passed along to `self.search_ext` unmodified (aside from adding a `Sync Request` control to any `serverctrls` provided).

`mode` provides `syncrepl` mode. Can be `'refreshOnly'` to finish after synchronization, or `'refreshAndPersist'` to persist (continue to receive updates) after synchronization.

`cookie`: an opaque value representing the replication state of the client. Subclasses should override the `syncrepl_set_cookie()` and `syncrepl_get_cookie()` methods to store the cookie appropriately, rather than passing it.

Only a single `syncrepl` search may be active on a `SyncreplConsumer` object. Multiple concurrent `syncrepl` searches require multiple separate `SyncreplConsumer` objects and thus multiple connections (`LDAPObject` instances).

syncrepl_set_cookie (*cookie*)

Called by `syncrepl_poll()` to store a new cookie provided by the server.

5.3.11 ldap.sasl SASL Authentication Methods

This module implements various authentication methods for SASL bind.

See also:

RFC 4422 - Simple Authentication and Security Layer (SASL) **RFC 4513** - Lightweight Directory Access Protocol (LDAP): Authentication Methods and Security Mechanisms

Constants

`ldap.sasl.CB_USER`

`ldap.sasl.CB_AUTHNAME`

`ldap.sasl.CB_LANGUAGE`

`ldap.sasl.CB_PASS`

`ldap.sasl.CB_ECHOPROMPT`

`ldap.sasl.CB_NOECHOPROMPT`

`ldap.sasl.CB_GETREALM`

Classes

class `ldap.sasl.sasl` (*cb_value_dict, mech*)

This class handles SASL interactions for authentication. If an instance of this class is passed to ldap's `sasl_bind_s()` method, the library will call its `callback()` method. For specific SASL authentication mechanisms, this method can be overridden

This class is used with `ldap.LDAPObject.sasl_interactive_bind_s()`.

callback (*cb_id, challenge, prompt, defresult*)

The callback method will be called by the `sasl_bind_s()` method several times. Each time it will provide the `id`, which tells us what kind of information is requested (the `CB_*` constants above). The `challenge` might be a short (English) text or some binary string, from which the return value is calculated. The `prompt` argument is always a human-readable description string; The `defresult` is a default value provided by the sasl library

Currently, we do not use the `challenge` and `prompt` information, and return only information which is stored in the `self.cb_value_dict` `cb_value_dictionary`. Note that the current callback interface is not very useful for writing generic sasl GUIs, which would need to know all the questions to ask, before the answers are returned to the sasl lib (in contrast to one question at a time).

Unicode strings are always converted to bytes.

class `ldap.sasl.cram_md5` (*authc_id, password, authz_id=""*)

This class handles SASL CRAM-MD5 authentication.

class `ldap.sasl.digest_md5` (*authc_id, password, authz_id=""*)

This class handles SASL DIGEST-MD5 authentication.

class `ldap.sasl.gssapi` (*authz_id=""*)

This class handles SASL GSSAPI (i.e. Kerberos V) authentication.

You might consider using convenience method `ldap.LDAPObject.sasl_gssapi_bind_s()`.

class `ldap.sasl.external` (*authz_id=""*)

This class handles SASL EXTERNAL authentication (i.e. X.509 client certificate)

You might consider using convenience method `ldap.LDAPObject.sasl_external_bind_s()`.

Examples for ldap.sasl

This example connects to an OpenLDAP server via LDAP over IPC (see [draft-chu-ldap-ldapi](#)) and sends a SASL external bind request.

```
import ldap, ldap.sasl, urllib

ldapi_path = '/tmp/openldap-socket'
ldap_conn = ldap.initialize(
    'ldapi://%s' % (
        urllib.quote_plus(ldapi_path)
    )
)
# Send SASL bind request for mechanism EXTERNAL
ldap_conn.sasl_non_interactive_bind_s('EXTERNAL')
# Find out the SASL Authorization Identity
print ldap_conn.whoami_s()
```

5.3.12 ldif LDIF parser and generator

This module parses and generates LDAP data in the format LDIF. It is implemented in pure Python and does not rely on any non-standard modules. Therefore it can be used stand-alone without the rest of the python-ldap package.

See also:

[RFC 2849](#) - The LDAP Data Interchange Format (LDIF) - Technical Specification

Functions

`ldif.CreateLDIF` (*dn, record, base64_attrs=None, cols=76*)

Create LDIF single formatted record including trailing empty line. This is a compatibility function.

dn string-representation of distinguished name

record Either a dictionary holding the LDAP entry {attrtype:record} or a list with a modify list like for `LDAPObject.modify()`.

base64_attrs list of attribute types to be base64-encoded in any case

cols Specifies how many columns a line may have before it's folded into many lines.

Deprecated since version 3.0: `ldif.CreateLDIF()` is deprecated. It will be removed in version 3.1. Use `ldif.LDIFWriter.unparse()` with a file or `io.StringIO` instead.

`ldif.ParseLDIF` (*f, ignore_attrs=None, maxentries=0*)

Parse LDIF records read from file. This is a compatibility function.

Deprecated since version 3.0: `ldif.ParseLDIF()` is deprecated. It will be removed in version 3.1. Use the `all_records` attribute of the returned value of `ldif.LDIFRecordList.parse()` instead.

Classes

class `ldap.LDIFWriter` (*output_file*, *base64_attrs=None*, *cols=76*, *line_sep='n'*)
 Write LDIF entry or change records to file object Copy LDIF input to a file output object containing all data retrieved via URLs

unparse (*dn*, *record*)

dn string-representation of distinguished name

record Either a dictionary holding the LDAP entry {attrtype:record} or a list with a modify list like for LDAPObject.modify().

class `ldap.LDIFParser` (*input_file*, *ignored_attr_types=None*, *max_entries=0*, *process_url_schemes=None*, *line_sep='n'*)
 Base class for a LDIF parser. Applications should sub-class this class and override method handle() to implement something meaningful.

Public class attributes:

records_read Counter for records processed so far

handle (*dn*, *entry*)
 Process a single content LDIF record. This method should be implemented by applications using LDIFParser.

handle_modify (*dn*, *modops*, *controls=None*)
 Process a single LDIF record representing a single modify operation. This method should be implemented by applications using LDIFParser.

parse ()
 Invokes LDIFParser.parse_entry_records() for backward compatibility

parse_entry_records ()
 Continuously read and parse LDIF entry records

class `ldap.LDIFRecordList` (*input_file*, *ignored_attr_types=None*, *max_entries=0*, *process_url_schemes=None*)
 Collect all records of a LDIF file. It can be a memory hog!

Records are stored in *all_records* as a single list of 2-tuples (dn, entry), after calling *parse()*.

all_records = None
 List storing parsed records.

handle (*dn*, *entry*)
 Append a single record to the list of all records (*all_records*).

handle_modify (*dn*, *modops*, *controls=None*)
 Process a single LDIF record representing a single modify operation. This method should be implemented by applications using LDIFParser.

class `ldap.LDIFCopy` (*input_file*, *output_file*, *ignored_attr_types=None*, *max_entries=0*, *process_url_schemes=None*, *base64_attrs=None*, *cols=76*, *line_sep='n'*)
 Copy LDIF input to LDIF output containing all data retrieved via URLs

handle (*dn*, *entry*)
 Write single LDIF record to output file.

Example

The following example demonstrates how to write LDIF output of an LDAP entry with *ldap* module.

```
>>> import sys, ldif
>>> entry={'objectClass': [b'top', b'person'], 'cn': [b'Michael Stroeder'], 'sn': [b
↳ 'Stroeder']}
>>> dn='cn=Michael Stroeder,ou=Test'
>>> ldif_writer=ldif.LDIFWriter(sys.stdout)
>>> ldif_writer.unparse(dn, entry)
dn: cn=Michael Stroeder,ou=Test
cn: Michael Stroeder
objectClass: top
objectClass: person
sn: Stroeder
```

The following example demonstrates how to parse an LDIF file with `ldif` module, skip some entries and write the result to stdout.

```
import sys
from ldif import LDIFParser, LDIFWriter

SKIP_DN = ["uid=foo,ou=People,dc=example,dc=com",
           "uid=bar,ou=People,dc=example,dc=com"]

class MyLDIF(LDIFParser):
    def __init__(self, input, output):
        LDIFParser.__init__(self, input)
        self.writer = LDIFWriter(output)

    def handle(self, dn, entry):
        if dn in SKIP_DN:
            return
        self.writer.unparse(dn, entry)

parser = MyLDIF(open("input.ldif", 'rb'), sys.stdout)
parser.parse()
```

5.3.13 ldapurl LDAP URL handling

This module parses and generates LDAP URLs. It is implemented in pure Python and does not rely on any non-standard modules. Therefore it can be used stand-alone without the rest of the python-ldap package.

See also:

RFC 4516 - The LDAP URL Format

Constants

The `ldapurl` module exports the following constants:

`ldapurl.SEARCH_SCOPE`

This dictionary maps a search scope string identifier to the corresponding integer value used with search operations in `ldap`.

`ldapurl.SEARCH_SCOPE_STR`

This dictionary is the inverse to `SEARCH_SCOPE`. It maps a search scope integer value to the corresponding string identifier used in a LDAP URL string representation.

`ldapurl.LDAP_SCOPE_BASE`

`ldapurl.LDAP_SCOPE_ONELEVEL`

`ldapurl.LDAP_SCOPE_SUBTREE`

Functions

`ldapurl.isLDAPUrl(s)`

Returns True if *s* is a LDAP URL, else False

`ldapurl.ldapUrlEscape(s)`

Returns URL encoding of string *s*

Classes

LDAP URLs

A `LDAPUrl` object represents a complete LDAP URL.

```
class ldapurl.LDAPUrl(ldapUrl=None, urlscheme='ldap', hostport="", dn="", attrs=None,
                      scope=None, filterstr=None, extensions=None, who=None, cred=None)
```

Class for parsing and unparsing LDAP URLs as described in RFC 4516.

Usable class attributes:

urlscheme URL scheme (either ldap, ldaps or ldapi)

hostport LDAP host (default '')

dn String holding distinguished name (default '')

attrs list of attribute types (default None)

scope integer search scope for ldap-module

filterstr String representation of LDAP Search Filters (see RFC 4515)

extensions Dictionary used as extensions store

who Maps automatically to bindname LDAP URL extension

cred Maps automatically to X-BINDPW LDAP URL extension

Changed in version 3.4.0: The `urlscheme` is now case insensitive and always converted to lower case. `LDAP://localhost` is equivalent to `ldap://localhost`.

applyDefaults (*defaults*)

Apply defaults to all class attributes which are None.

defaults Dictionary containing a mapping from class attributes to default values

htmlHREF (*urlPrefix=""*, *hrefText=None*, *hrefTarget=None*)

Returns a string with HTML link for this LDAP URL.

urlPrefix Prefix before LDAP URL (e.g. for addressing another web-based client)

hrefText link text/description

hrefTarget string added as link target attribute

initializeUrl ()

Returns LDAP URL suitable to be passed to `ldap.initialize()`

unparse()
Returns LDAP URL depending on class attributes set.

LDAP URL extensions

A *LDAPUrlExtension* object represents a single LDAP URL extension whereas *LDAPUrlExtensions* represents a list of LDAP URL extensions.

class ldapurl.LDAPUrlExtension (*extensionStr=None, critical=0, extype=None, exvalue=None*)
Class for parsing and unarsing LDAP URL extensions as described in RFC 4516.

Usable class attributes:

critical Boolean integer marking the extension as critical
extype Type of extension
exvalue Value of extension

class ldapurl.LDAPUrlExtensions (*default=None*)
Models a collection of LDAP URL extensions as a mapping type

Example

Important security advice: For security reasons you should not specify passwords in LDAP URLs unless you really know what you are doing.

The following example demonstrates how to parse a LDAP URL with *ldapurl* module.

```
>>> import ldapurl
>>> ldap_url = ldapurl.LDAPUrl('ldap://localhost:1389/dc=stroeder,dc=com?cn,mail??
↳bindname=cn=Michael%2cdc=stroeder%2cdc=com,X-BINDPW=secret')
>>> # Using the parsed LDAP URL by reading the class attributes
>>> ldap_url.dn
'dc=stroeder,dc=com'
>>> ldap_url.hostport
'localhost:1389'
>>> ldap_url.attrs
['cn', 'mail']
>>> ldap_url.filterstr
'(objectclass=*)'
>>> ldap_url.who
'cn=Michael,dc=stroeder,dc=com'
>>> ldap_url.cred
'secret'
>>> ldap_url.scope
0
```

The following example demonstrates how to generate a LDAP URL with module{ldapurl} module.

```
>>> import ldapurl
>>> ldap_url = ldapurl.LDAPUrl(hostport='localhost:1389', dn='dc=stroeder,dc=com',
↳attrs=['cn', 'mail'], who='cn=Michael,dc=stroeder,dc=com', cred='secret')
>>> ldap_url.unparse()
'ldap://localhost:1389/dc=stroeder,dc=com?cn,mail?base?(objectclass=*)?
↳bindname=cn=Michael%2Cdc=stroeder%2Cdc=com,X-BINDPW=secret'
```

5.3.14 slapdtest Spawning test instances of OpenLDAP's slapd server

The module is used for testing python-ldap itself but can be used for automatically testing any OpenLDAP-based configuration setup.

This module is pure Python and does not rely on any non-standard modules. Therefore it can be used stand-alone without the rest of the python-ldap package.

Test fixtures for the popular *pytest* framework are developed in an external project, [pytest-ldap](#).

Functions

Classes

class slapdtest.SlapdObject

Controller class for a slapd instance, OpenLDAP's server.

This class creates a temporary data store for slapd, runs it listening on a private Unix domain socket and TCP port, and initializes it with a top-level entry and the root user.

When a reference to an instance of this class is lost, the slapd server is shut down.

An instance can be used as a context manager. When exiting the context manager, the slapd server is shut down and the temporary data store is removed.

Parameters `openldap_schema_files` – A list of schema names or schema paths to load at startup. By default this only contains *core*.

Changed in version 3.1: Added context manager functionality

gen_config ()

generates a slapd.conf and returns it as one string

for generating specific static configuration files you have to override this method

ldapadd (*ldif*, *extra_args=None*)

Runs ldapadd on this slapd instance, passing it the ldif content

ldapdelete (*dn*, *recursive=False*, *extra_args=None*)

Runs ldapdelete on this slapd instance, deleting 'dn'

ldapmodify (*ldif*, *extra_args=None*)

Runs ldapadd on this slapd instance, passing it the ldif content

ldapwhoami (*extra_args=None*)

Runs ldapwhoami on this slapd instance

restart ()

Restarts the slapd server with same data

setup_rundir ()

creates rundir structure

for setting up a custom directory structure you have to override this method

slapadd (*ldif*, *extra_args=None*)

Runs slapadd on this slapd instance, passing it the ldif content

start ()

Starts the slapd server process running, and waits for it to come up.

stop ()

Stops the slapd server, and waits for it to terminate and cleans up

wait ()

Waits for the slapd process to terminate by itself.

class slapdtest.SlapdTestCase (*methodName='runTest'*)

test class which also clones or initializes a running slapd

server_class

alias of *SlapdObject*

classmethod setUpClass ()

Hook method for setting up class fixture before running tests in the class.

classmethod tearDownClass ()

Hook method for deconstructing the class fixture after running all tests in the class.

5.4 Third-party documentation

The following documents referenced are not written by python-ldap project members. Therefore some information might be outdated or links might be broken.

5.4.1 *Python LDAP Applications* articles by Matt Butcher

- [Part 1 - Installing and Configuring the Python-LDAP Library and Binding to an LDAP Directory](#)

This also covers SASL.

- [Part 2 - LDAP Operations](#)
- [Part 3 - More LDAP Operations and the LDAP URL Library](#)
- [Part 4 - LDAP Schema](#)

Gee, someone waded through the badly documented mysteries of module *ldap.schema*.

5.4.2 LDAP Programming in Python

Another article for getting started with python-ldap.

5.4.3 RFC 1823

The LDAP Application Program Interface, mainly for LDAPv2.

5.4.4 LDAPEXT draft

The Internet draft of the discontinued IETF working group LDAPEXT is of interest here since the OpenLDAP 2 libs implement this (expired) draft.

5.4.5 OpenLDAP

It's worth to have a look at the [manual pages](#) and the [Developer's FAQ](#).

5.4.6 VSLDAP

VSLDAP Interoperability Test Suite.

5.5 Contributing to python-ldap

Thank you for your interest in python-ldap! If you'd like to contribute (be it code, documentation, maintenance effort, or anything else), this guide is for you.

5.5.1 Sample workflow for python-ldap development

This document will guide you through the process of contributing a change to python-ldap.

We assume that, as a user of python-ldap, you're not new to software development in general, so these instructions are terse. If you need additional detail, please do ask on the mailing list.

Note: The following instructions are for Linux. If you can translate them to another system, please contribute your translation!

Install `Git`, `tox` and the *Build prerequisites*.

Clone the repository:

```
$ git clone https://github.com/python-ldap/python-ldap
$ cd python-ldap
```

Create a `virtual environment` to ensure you in-development python-ldap won't affect the rest of your system:

```
$ python3 -m venv __venv__
```

Activate the virtual environment:

```
$ source __venv__/bin/activate
```

Install python-ldap to it in `editable mode`:

```
(__venv__$ python -m pip install -e .
```

This way, importing a Python module from python-ldap will directly use the code from your source tree. If you change C code, you will still need to recompile (using the `pip install` command again).

Change the code as desired.

To run tests, install and run `tox`:

```
(__venv__$ python -m pip install tox
(__venv__$ tox --skip-missing-interpreters
```

This will run tests on all supported versions of Python that you have installed, skipping the ones you don't. To run a subset of test environments, run for example:

```
(__venv__$ tox -e py36,py39
```

In addition to `pyXY` environments, we have extra environments for checking things independent of the Python version:

- `doc` checks syntax and spelling of the documentation
- `coverage-report` generates a test coverage report for Python code. It must be used last, e.g. `tox -e py36,py39,coverage-report`.
- `py3-nosasl_tls` check functionality without SASL and TLS bindings compiled in.

When your change is ready, commit to Git, and submit a pull request on GitHub. You can take a look at the *Instructions for core committers* to see what we are looking for in a pull request.

If you don't want to open a GitHub account, please send patches as attachments to the python-ldap mailing list.

5.5.2 Communication

Always keep in mind that python-ldap is developed and maintained by volunteers. We're happy to share our work, and to work with you to make the library better, but (until you pay someone), there's obligation to provide assistance.

So, keep it friendly, respectful, and supportive!

Mailing list

Discussion about the use and future of python-ldap occurs in the `python-ldap@python.org` mailing list.

It's also the channel to use if documentation (including this guide) is not clear to you. Do try searching around before you ask on the list, though!

You can [subscribe](#) or [unsubscribe](#) to this list or browse the [list archive](#).

Issues

Please report bugs, missing features and other issues to [the bug tracker](#) at GitHub. You will need a GitHub account for that.

If you prefer not to open a GitHub account, you're always welcome to use the mailing list.

Security Contact

If you found a security issue that should not be discussed publicly, please e-mail the maintainer at `pviktori@redhat.com`. If required, write to coordinate a more secure channel.

All other communication should be public.

5.5.3 Contributing code

If you're used to open-source Python development with Git, here's the gist:

- `git clone https://github.com/python-ldap/python-ldap`
- Use GitHub for [the bug tracker](#) and pull requests.
- Run tests with `tox`; ignore Python interpreters you don't have locally.

Or, if you prefer to avoid closed-source services:

- `git clone https://pagure.io/python-ldap`
- Send bug reports and patches to the mailing list.

- Run tests with `tox`; ignore Python interpreters you don't have locally.
- Read the documentation directly at [Read the Docs](#).

If you're new to some aspect of the project, you're welcome to use (or adapt) our [sample workflow](#).

5.5.4 Additional tests and scripts

We use several specialized tools for debugging and maintenance.

Make targets

Make targets currently use the `python3` executable. Specify a different one using, for example:

```
make PYTHON=/usr/local/bin/python
```

Notable targets are:

make autoformat Automatically re-formats C and Python code to conform to Python style guides (PEP 7 and PEP 8). Note that no backups are made – please commit any other changes before using this target.

Requires the `indent` program and the `black` Python module.

make lcov lcov-open Generate and view test coverage for C code. Requires `LCOV`.

make scan-build Run static analysis. Requires `clang`.

make valgrind Run `Valgrind` to check for memory leaks. Requires `valgrind` and a Python suppression file, which you can specify as `PYTHON_SUPP`, e.g.:

```
make valgrind PYTHON_SUPP=/your/path/to/valgrind-python.supp
```

The suppression file is `Misc/valgrind-python.supp` in the Python source distribution, and it's frequently packaged together with Python development headers.

Reference leak tests

Reference leak tests require a `pydebug` build of CPython and `pytest` with `pytest-leaks` plugin. A `pydebug` build has a global reference counter, which keeps track of all reference increments and decrements. The leak plugin runs each test multiple times and checks if the reference count increases.

Download and compile the `pydebug` build:

```
$ curl -O https://www.python.org/ftp/python/3.6.3/Python-3.6.3.tar.xz
$ tar xJf Python-3.6.3.tar.xz
$ cd Python-3.6.3
$ ./configure --with-pydebug
$ make
```

Create a virtual environment with the `pydebug` build:

```
$ ./python -m venv /tmp/refleak
$ /tmp/refleak/bin/pip install pytest pytest-leaks
```

Run reference leak tests:

```
$ cd path/to/python-ldap
$ /tmp/refleak/bin/pip install --upgrade .
$ /tmp/refleak/bin/pytest -v -R:
```

Run `/tmp/refleak/bin/pip install --upgrade .` every time a file outside of `Tests/` is modified.

5.5.5 Instructions for core committers

If you have the authority (and responsibility) of merging changes from others, remember:

- All code changes need to be reviewed by someone other than the author.
- Tests must always pass. New features without tests shall *not* pass review.
- Make sure commit messages don't use GitHub-specific link syntax. Use the full URL, e.g. `https://github.com/python-ldap/python-ldap/issues/50` instead of `#20`.
 - Exception: it's fine to use the short form in the summary line of a merge commit, if the full URL appears later.
 - It's OK to use shortcuts in GitHub *discussions*, where they are not hashed into immutable history.
- Make a merge commit if the contribution contains several well-isolated separate commits with good descriptions. Use *squash-and-merge* (or *fast-forward* from a command line) for all other cases.
- It's OK to push small changes into a pull request. If you do this, document what you have done (so the contributor can learn for the future), and get their ACK (confirmation) before merging.
- When squashing, do edit commit messages to add references to the pull request and relevant discussions/issues, and to conform to Git best practices.
 - Consider making the summary line suitable for the CHANGES document, and starting it with a prefix like `Lib:` or `Tests:`.
- Push to Pagure as well.

If you have good reason to break the “rules”, go ahead and break them, but mention why.

5.5.6 Instructions for release managers

If you are tasked with releasing python-ldap, remember to:

- Bump all instances of the version number.
- Go through all changes since last version, and add them to CHANGES.
- Run *Additional tests and scripts* as appropriate, fix any regressions.
- Change the release date in CHANGES.
- Update `__version__` tags where appropriate (each module `ldap`, `ldif`, `ldapurl`, `slapdtest` has its own copy).
- Merge all that (using pull requests).
- Run `python setup.py sdist`, and smoke-test the resulting package (install in a clean virtual environment, `import ldap`).
- Create GPG-signed Git tag: `git tag -s python-ldap-{version}`. Push it to GitHub and Pagure.
- Release the `sdist` on PyPI.

- Announce the release on the mailing list. Mention the Git hash.
- Add the release’s log from CHANGES on the [GitHub release page](#).
- Check that python-ldap.org shows the latest version; if not, adjust things at [readthedocs.org](#)

5.6 python-ldap FAQ

5.6.1 Project

Q: Is python-ldap yet another abandon-ware project?

A1: “Jump on in.”

A2: “Jump into the C ;-)”

A3: see file CHANGES in source distribution or [repository](#).

5.6.2 Usage

Q: Does it work with Python 3?

A0: Yes, from 3.0 on.

A1: For earlier versions, there’s [pyldap](#), an independent fork now merged into python-ldap.

Q: Does it work with Python 2.7? (1.5|2.0|2.1|2.2|2.3|2.4|2.5|2.6|2.7)?

A: No. Old versions of python-ldap are still available from PyPI, though.

Q: My code imports module `_ldap`. That used to work, but after an upgrade it does not work anymore. Why?

A: **Despite some outdated programming examples, the extension module `_ldap` MUST NOT** be imported directly, unless you really know what you’re doing (e.g. for internal regression testing).

Import `ldap` instead, which is a Python wrapper around `_ldap` providing the full functionality.

Q: My script bound to MS Active Directory but a a search operation results in the exception `ldap.OPERATIONS_ERROR` with the diagnostic message text “*In order to perform this operation a successful bind must be completed on the connection.*” Alternatively, a Samba 4 AD returns the diagnostic message “*Operation unavailable without authentication*”. What’s happening here?

A: When searching from the domain level, MS AD returns referrals (search continuations) for some objects to indicate to the client where to look for these objects. Client-chasing of referrals is a broken concept, since LDAPv3 does not specify which credentials to use when chasing the referral. Windows clients are supposed to simply use their Windows credentials, but this does not work in general when chasing referrals received from and pointing to arbitrary LDAP servers.

Therefore, per default, `libldap` automatically chases the referrals internally with an *anonymous* access which fails with MS AD.

So, the best thing to do is to switch this behaviour off:

```
l = ldap.initialize('ldap://foobar')
l.set_option(ldap.OPT_REFERRALS, 0)
```

Note that setting the above option does NOT prevent search continuations from being returned, rather only that `libldap` won’t attempt to resolve referrals.

Q: Why am I seeing a `ldap.SUCCESS` traceback as output?

A: Most likely, you are using one of the non-synchronous calls, and probably mean to be using a synchronous call (see detailed explanation in *Sending LDAP requests*).

Q: Can I use LDAPv2 via python-ldap?

A: Yes, by explicitly setting the class attribute `protocol_version`.

You should not do that nowadays since `LDAPv2` is considered historic since many years.

Q: My TLS settings are ignored/TLS isn't working?

A: Make sure you call `set_option(ldap.OPT_X_TLS_NEWCTX, 0)` after changing any of the `OPT_X_TLS_*` options.

5.6.3 Installing

Q: Does it work with Windows 32?

A: Yes. You can find links to unofficial pre-compiled packages for Windows on the *Installing python-ldap* page.

Q: Can python-ldap be built against OpenLDAP 2.3 libs or older?

A: No. The needed minimal version of OpenLDAP is documented in *Build prerequisites*. Patched builds of python-ldap linked to older libs are not supported by the python-ldap project.

Q: During build there are warning messages displayed telling `Lib/ldap.py` and `Lib/ldap/schema.py` are not found:

```
warning: build_py: file Lib/ldap.py (for module ldap) not found
warning: build_py: file Lib/ldap/schema.py (for module ldap.schema) not found
```

A: `ldap` and `ldap.schema` are both module packages (directories containing various sub-modules). The messages above are falsely produced by `DistUtils`. Don't worry about it.

Q: What's the correct way to install on macOS?

A:

```
xcode-select --install
pip install python-ldap \
  --global-option=build_ext \
  --global-option="-I$(xcrun --show-sdk-path)/usr/include/sasl"
```

Q: While importing module `ldap`, some shared lib files are not found. The error message looks similar to this:

```
ImportError: ld.so.1: /usr/local/bin/python: fatal: liblber.so.2: open failed: No_
↪such file or directory
```

A1: You need to make sure that the path to `liblber.so.2` and `libldap.so.2` is in your `LD_LIBRARY_PATH` environment variable.

A2: Alternatively, if you're on Linux, you can add the path to `liblber.so.2` and `libldap.so.2` to `/etc/ld.so.conf` and invoke the command `ldconfig` afterwards.

5.6.4 Historic

Q: Can python-ldap 2.x be built against Netscape, Mozilla or Novell libs?

A: Nope.

Q: My binary version of python-ldap was build with LDAP libs 3.3. But the python-ldap docs say LDAP libs 2.x are needed. I'm confused!

Short answer: See answer above and the [Installing python-ldap](#) page for a more recent version.

Long answer: E.g. some Win32 DLLs floating around for download are based on the old Umich LDAP code which is not maintained anymore for *many* years! Last Umich 3.3 release was 1997 if I remember correctly.

The OpenLDAP project took over the Umich code and started releasing OpenLDAP 1.x series mainly fixing bugs and doing some improvements to the database backend. Still, only LDAPv2 was supported at server and client side. (Many commercial vendors also derived their products from the Umich code.)

OpenLDAP 2.x is a full-fledged LDAPv3 implementation. It has its roots in Umich code but has many more features/improvements.

Q: While importing module ldap, there are undefined references reported. The error message looks similar to this:

```
ImportError: /usr/local/lib/libldap.so.2: undefined symbol: res_query
```

A: Especially on older Linux systems, you might have to explicitly link against libresolv.

Tweak `setup.cfg` to contain this line:

```
libs = lber ldap resolv
```


CHAPTER 6

Indices and tables

- `genindex`
- `modindex`
- `search`

I

ldap (*Posix, Windows*), 13
ldap.asyncsearch, 30
ldap.controls, 33
ldap.controls.libldap, 36
ldap.controls.ppolicy, 38
ldap.controls.psearch, 36
ldap.controls.readentry, 38
ldap.controls.sessiontrack, 37
ldap.controls.simple, 34
ldap.dn, 39
ldap.extop, 40
ldap.extop.dds, 40
ldap.filter, 41
ldap.modlist, 41
ldap.resiter, 42
ldap.sasl, 49
ldap.schema, 43
ldap.schema.models, 44
ldap.schema.subentry, 43
ldap.syncrepl, 47
ldapurl, 52
ldif, 50

S

slapdtest, 55

A

abandon() (*ldap.LDAPObject method*), 23
 abandon_ext() (*ldap.LDAPObject method*), 23
 add() (*ldap.LDAPObject method*), 23
 add_ext() (*ldap.LDAPObject method*), 23
 add_ext_s() (*ldap.LDAPObject method*), 24
 add_s() (*ldap.LDAPObject method*), 23
 addModlist() (*in module ldap.modlist*), 41
 ADMINLIMIT_EXCEEDED, 19
 AFFECTS_MULTIPLE_DSAS, 19
 afterFirstResult()
 (*ldap.asyncsearch.AsyncSearchHandler method*), 31
 ALIAS_DEREF_PROBLEM, 19
 ALIAS_PROBLEM, 20
 all_records (*ldif.LDIFRecordList attribute*), 51
 allresults() (*ldap.resiter.ResultProcessor method*), 42
 ALREADY_EXISTS, 20
 applyDefaults() (*ldapurl.LDAPUrl method*), 53
 AssertionControl (*class in ldap.controls.libldap*), 36
 AsyncSearchHandler (*class in ldap.asyncsearch*), 31
 attribute_types() (*ldap.schema.models.Entry method*), 44
 attribute_types()
 (*ldap.schema.subentry.SubSchema method*), 43
 AttributeType (*class in ldap.schema.models*), 45
 AUTH_UNKNOWN, 20
 AuthorizationIdentityRequestControl
 (*class in ldap.controls.simple*), 35
 AuthorizationIdentityResponseControl
 (*class in ldap.controls.simple*), 35

B

bind() (*ldap.LDAPObject method*), 24
 bind_s() (*ldap.LDAPObject method*), 24
 BooleanControl (*class in ldap.controls.simple*), 34

BUSY, 20

C

callback() (*ldap.sasl.sasl method*), 49
 cancel() (*ldap.LDAPObject method*), 24
 CB_AUTHNAME (*in module ldap.sasl*), 49
 CB_ECHOPROMPT (*in module ldap.sasl*), 49
 CB_GETREALM (*in module ldap.sasl*), 49
 CB_LANGUAGE (*in module ldap.sasl*), 49
 CB_NOECHOPROMPT (*in module ldap.sasl*), 49
 CB_PASS (*in module ldap.sasl*), 49
 CB_USER (*in module ldap.sasl*), 49
 CLIENT_LOOP, 20
 compare() (*ldap.LDAPObject method*), 24
 compare_ext() (*ldap.LDAPObject method*), 24
 compare_ext_s() (*ldap.LDAPObject method*), 24
 COMPARE_FALSE, 20
 compare_s() (*ldap.LDAPObject method*), 24
 COMPARE_TRUE, 20
 CONFIDENTIALITY_REQUIRED, 20
 CONNECT_ERROR, 20
 CONSTRAINT_VIOLATION, 20
 CONTROL_NOT_FOUND, 20
 cram_md5 (*class in ldap.sasl*), 49
 CreateLDIF() (*in module ldif*), 50

D

DecodeControlTuples() (*in module ldap.controls*), 34
 decodeControlValue()
 (*ldap.controls.libldap.SimplePagedResultsControl method*), 36
 decodeControlValue()
 (*ldap.controls.ppolicy.PasswordPolicyControl method*), 39
 decodeControlValue()
 (*ldap.controls.psearch.EntryChangeNotificationControl method*), 37

- `decodeControlValue()`
(ldap.controls.readentry.ReadEntryControl method), 38
- `decodeControlValue()`
(ldap.controls.ResponseControl method), 33
- `decodeControlValue()`
(ldap.controls.simple.AuthorizationIdentityResponseControl method), 35
- `decodeControlValue()`
(ldap.controls.simple.BooleanControl method), 35
- `decodeControlValue()`
(ldap.controls.simple.OctetStringInteger method), 34
- `decodeResponseValue()`
(ldap.extop.dds.RefreshResponse method), 41
- `decodeResponseValue()`
(ldap.extop.ExtendedResponse method), 40
- DECODING_ERROR**, 20
- `delete()` *(ldap.LDAPObject method), 24*
- `delete_ext()` *(ldap.LDAPObject method), 24*
- `delete_ext_s()` *(ldap.LDAPObject method), 24*
- `delete_s()` *(ldap.LDAPObject method), 24*
- Dict** *(class in ldap.asyncsearch), 31*
- digest_md5** *(class in ldap.sasl), 49*
- DITContentRule** *(class in ldap.schema.models), 46*
- DITStructureRule** *(class in ldap.schema.models), 47*
- `dn2str()` *(in module ldap.dn), 39*
- DN_FORMAT_AD_CANONICAL** *(in module ldap), 19*
- DN_FORMAT_DCE** *(in module ldap), 19*
- DN_FORMAT_LDAP** *(in module ldap), 19*
- DN_FORMAT_LDAPV2** *(in module ldap), 19*
- DN_FORMAT_LDAPV3** *(in module ldap), 19*
- DN_FORMAT_MASK** *(in module ldap), 19*
- DN_FORMAT_UFN** *(in module ldap), 19*
- DN_P_NOLEADTRAILSPACES** *(in module ldap), 19*
- DN_P_NOSPACEAFTERRDN** *(in module ldap), 19*
- DN_PEDANTIC** *(in module ldap), 19*
- DN_PRETTY** *(in module ldap), 19*
- DN_SKIP** *(in module ldap), 19*
- E**
- `encodeControlValue()`
(ldap.controls.libldap.AssertionControl method), 36
- `encodeControlValue()`
(ldap.controls.libldap.MatchedValuesControl method), 36
- `encodeControlValue()`
(ldap.controls.libldap.SimplePagedResultsControl method), 36
- `encodeControlValue()`
(ldap.controls.psearch.PersistentSearchControl method), 37
- `encodeControlValue()`
(ldap.controls.readentry.ReadEntryControl method), 38
- `encodeControlValue()`
(ldap.controls.RequestControl method), 33
- `encodeControlValue()`
(ldap.controls.sessiontrack.SessionTrackingControl method), 37
- `encodeControlValue()`
(ldap.controls.simple.BooleanControl method), 35
- `encodeControlValue()`
(ldap.controls.simple.OctetStringInteger method), 34
- `encodeControlValue()`
(ldap.controls.simple.ValueLessRequestControl method), 34
- `encodedRequestValue()`
(ldap.extop.dds.RefreshRequest method), 41
- `encodedRequestValue()`
(ldap.extop.ExtendedRequest method), 40
- ENCODING_ERROR**, 20
- Entry** *(class in ldap.schema.models), 44*
- EntryChangeNotificationControl** *(class in ldap.controls.psearch), 37*
- error** *(ldap.controls.ppolicy.PasswordPolicyControl attribute), 39*
- `escape_dn_chars()` *(in module ldap.dn), 39*
- `escape_filter_chars()` *(in module ldap.filter), 41*
- `explode_dn()` *(in module ldap.dn), 39*
- `explode_rdn()` *(in module ldap.dn), 39*
- ExtendedRequest** *(class in ldap.extop), 40*
- ExtendedResponse** *(class in ldap.extop), 40*
- external** *(class in ldap.sasl), 49*
- `extop()` *(ldap.LDAPObject method), 24*
- `extop_result()` *(ldap.LDAPObject method), 25*
- `extop_s()` *(ldap.LDAPObject method), 24*
- extra_compile_args** *(built-in variable), 11*
- extra_objects** *(built-in variable), 12*
- F**
- FILTER_ERROR**, 20
- `filter_format()` *(in module ldap.filter), 41*
- G**
- `gen_config()` *(slapdtest.SlapdObject method), 55*
- `get_applicable_aux_classes()`
(ldap.schema.subentry.SubSchema method), 44

- get_inheritedattr() (*ldap.schema.subentry.SubSchema method*), 44
 get_inheritedobj() (*ldap.schema.subentry.SubSchema method*), 44
 get_obj() (*ldap.schema.subentry.SubSchema method*), 44
 get_option() (*in module ldap*), 14
 get_option() (*ldap.LDAPObject method*), 29
 get_structural_oc() (*ldap.schema.subentry.SubSchema method*), 44
 get_syntax() (*ldap.schema.subentry.SubSchema method*), 44
 GetEffectiveRightsControl (*class in ldap.controls.simple*), 35
 getoid() (*ldap.schema.subentry.SubSchema method*), 44
 graceAuthNsRemaining (*ldap.controls.ppolicy.PasswordPolicyControl attribute*), 38
 gssapi (*class in ldap.sasl*), 49
- ## H
- handle() (*ldif.LDIFCopy method*), 51
 handle() (*ldif.LDIFParser method*), 51
 handle() (*ldif.LDIFRecordList method*), 51
 handle_modify() (*ldif.LDIFParser method*), 51
 handle_modify() (*ldif.LDIFRecordList method*), 51
 htmlHREF() (*ldapurl.LDAPUrl method*), 53
- ## I
- INAPPROPRIATE_AUTH, 20
 INAPPROPRIATE_MATCHING, 20
 include_dirs (*built-in variable*), 11
 IndexedDict (*class in ldap.asyncsearch*), 31
 INIT_FD_AVAIL (*in module ldap*), 14
 initialize() (*in module ldap*), 13
 initializeUrl() (*ldapurl.LDAPUrl method*), 53
 INSUFFICIENT_ACCESS, 20
 INVALID_CREDENTIALS, 20
 INVALID_DN_SYNTAX, 20
 INVALID_SYNTAX, 20
 is_dn() (*in module ldap.dn*), 39
 IS_LEAF, 20
 isLDAPUrl() (*in module ldapurl*), 53
 items() (*ldap.schema.models.Entry method*), 44
- ## K
- keys() (*ldap.schema.models.Entry method*), 44
 KNOWN_RESPONSE_CONTROLS (*in module ldap.controls*), 33
- ## L
- ldap (*module*), 13
- ldap.asyncsearch (*module*), 30
 ldap.controls (*module*), 33
 ldap.controls.libldap (*module*), 36
 ldap.controls.ppolicy (*module*), 38
 ldap.controls.psearch (*module*), 36
 ldap.controls.readentry (*module*), 38
 ldap.controls.sessiontrack (*module*), 37
 ldap.controls.simple (*module*), 34
 ldap.dn (*module*), 39
 ldap.extop (*module*), 40
 ldap.extop.dds (*module*), 40
 ldap.filter (*module*), 41
 ldap.ldapobject.LDAPObject (*class in ldap*), 22
 ldap.modlist (*module*), 41
 ldap.resiter (*module*), 42
 ldap.sasl (*module*), 49
 ldap.schema (*module*), 43
 ldap.schema.models (*module*), 44
 ldap.schema.subentry (*module*), 43
 ldap.syncrepl (*module*), 47
 ldap_entry() (*ldap.schema.subentry.SubSchema method*), 44
 LDAP_SCOPE_BASE (*in module ldapurl*), 52
 LDAP_SCOPE_ONELEVEL (*in module ldapurl*), 52
 LDAP_SCOPE_SUBTREE (*in module ldapurl*), 53
 ldapadd() (*slapdtest.SlapdObject method*), 55
 LDAPBytesWarning (*class in ldap*), 22
 LDAPControl (*class in ldap.controls*), 33
 ldapdelete() (*slapdtest.SlapdObject method*), 55
 LDAPError, 19
 ldapmodify() (*slapdtest.SlapdObject method*), 55
 LDAPUrl (*class in ldapurl*), 53
 ldapurl (*module*), 52
 ldapUrlEscape() (*in module ldapurl*), 53
 LDAPUrlExtension (*class in ldapurl*), 54
 LDAPUrlExtensions (*class in ldapurl*), 54
 ldapwhoami() (*slapdtest.SlapdObject method*), 55
 ldif (*module*), 50
 LDIFCopy (*class in ldif*), 51
 LDIFParser (*class in ldif*), 51
 LDIFRecordList (*class in ldif*), 51
 LDIFWriter (*class in ldap.asyncsearch*), 31
 LDIFWriter (*class in ldif*), 51
 library_dirs (*built-in variable*), 11
 libs (*built-in variable*), 11
 List (*class in ldap.asyncsearch*), 31
 listall() (*ldap.schema.subentry.SubSchema method*), 44
 LOCAL_ERROR, 21
 LOOP_DETECT, 21
- ## M
- ManageDSAITControl (*class in ldap.controls.simple*), 35

- MatchedValuesControl (class in *ldap.controls.libldap*), 36
- MatchingRule (class in *ldap.schema.models*), 46
- MatchingRuleUse (class in *ldap.schema.models*), 46
- modify() (*ldap.LDAPObject* method), 25
- modify_ext() (*ldap.LDAPObject* method), 25
- modify_ext_s() (*ldap.LDAPObject* method), 25
- modify_s() (*ldap.LDAPObject* method), 25
- modifyModlist() (in module *ldap.modlist*), 41
- modrdn() (*ldap.LDAPObject* method), 25
- modrdn_s() (*ldap.LDAPObject* method), 25
- MORE_RESULTS_TO_RETURN, 21
- ## N
- NameForm (class in *ldap.schema.models*), 46
- NAMING_VIOLATION, 21
- NO_MEMORY, 21
- NO_OBJECT_CLASS_MODS, 21
- NO_RESULTS_RETURNED, 21
- NO_SUCH_ATTRIBUTE, 21
- NO_SUCH_OBJECT, 21
- NOT_ALLOWED_ON_NONLEAF, 21
- NOT_ALLOWED_ON_RDN, 21
- NOT_HUMAN_READABLE_LDAP_SYNTAXES (in module *ldap.schema.subentry*), 43
- NOT_SUPPORTED, 21
- ## O
- OBJECT_CLASS_VIOLATION, 21
- ObjectClass (class in *ldap.schema.models*), 45
- OctetStringInteger (class in *ldap.controls.simple*), 34
- OPERATIONS_ERROR, 21
- OPT_API_FEATURE_INFO (in module *ldap*), 15
- OPT_API_INFO (in module *ldap*), 15
- OPT_CLIENT_CONTROLS (in module *ldap*), 15
- OPT_DEBUG_LEVEL (in module *ldap*), 15
- OPT_DEFBASE (in module *ldap*), 15
- OPT_DEREF (in module *ldap*), 15
- OPT_DIAGNOSTIC_MESSAGE (in module *ldap*), 15
- OPT_ERROR_STRING (in module *ldap*), 15
- OPT_HOST_NAME (in module *ldap*), 15
- OPT_MATCHED_DN (in module *ldap*), 15
- OPT_NETWORK_TIMEOUT (in module *ldap*), 15
- OPT_PROTOCOL_VERSION (in module *ldap*), 15
- OPT_REFERRALS (in module *ldap*), 15
- OPT_REFHOPLIMIT (in module *ldap*), 15
- OPT_RESTART (in module *ldap*), 15
- OPT_SERVER_CONTROLS (in module *ldap*), 15
- OPT_SIZELIMIT (in module *ldap*), 15
- OPT_SUCCESS (in module *ldap*), 15
- OPT_TIMELIMIT (in module *ldap*), 15
- OPT_TIMEOUT (in module *ldap*), 15
- OPT_URI (in module *ldap*), 15
- OPT_X_KEEPA_LIVE_IDLE (in module *ldap*), 18
- OPT_X_KEEPA_LIVE_INTERVAL (in module *ldap*), 18
- OPT_X_KEEPA_LIVE_PROBES (in module *ldap*), 18
- OPT_X_SASL_AUTHCID (in module *ldap*), 15
- OPT_X_SASL_AUTHZID (in module *ldap*), 15
- OPT_X_SASL_MECH (in module *ldap*), 15
- OPT_X_SASL_NOCANON (in module *ldap*), 15
- OPT_X_SASL_REALM (in module *ldap*), 15
- OPT_X_SASL_SECPROPS (in module *ldap*), 15
- OPT_X_SASL_SSF (in module *ldap*), 16
- OPT_X_SASL_SSF_EXTERNAL (in module *ldap*), 16
- OPT_X_SASL_SSF_MAX (in module *ldap*), 16
- OPT_X_SASL_SSF_MIN (in module *ldap*), 16
- OPT_X_TLS (in module *ldap*), 18
- OPT_X_TLS_ALLOW (in module *ldap*), 17
- OPT_X_TLS_CACERTDIR (in module *ldap*), 16
- OPT_X_TLS_CACERTFILE (in module *ldap*), 16
- OPT_X_TLS_CERTFILE (in module *ldap*), 16
- OPT_X_TLS_CIPHER (in module *ldap*), 17
- OPT_X_TLS_CIPHER_SUITE (in module *ldap*), 17
- OPT_X_TLS_CRL_ALL (in module *ldap*), 16
- OPT_X_TLS_CRL_NONE (in module *ldap*), 16
- OPT_X_TLS_CRL_PEER (in module *ldap*), 17
- OPT_X_TLS_CRLCHECK (in module *ldap*), 16
- OPT_X_TLS_CRLFILE (in module *ldap*), 16
- OPT_X_TLS_CTX (in module *ldap*), 17
- OPT_X_TLS_DEMAND (in module *ldap*), 17
- OPT_X_TLS_HARD (in module *ldap*), 17
- OPT_X_TLS_KEYFILE (in module *ldap*), 16
- OPT_X_TLS_NEVER (in module *ldap*), 17
- OPT_X_TLS_NEWCTX (in module *ldap*), 16
- OPT_X_TLS_PACKAGE (in module *ldap*), 16
- OPT_X_TLS_PEER_CERT (in module *ldap*), 17
- OPT_X_TLS_PROTOCOL_MAX (in module *ldap*), 18
- OPT_X_TLS_PROTOCOL_MIN (in module *ldap*), 18
- OPT_X_TLS_PROTOCOL_SSL3 (in module *ldap*), 18
- OPT_X_TLS_PROTOCOL_TLS1_0 (in module *ldap*), 18
- OPT_X_TLS_PROTOCOL_TLS1_1 (in module *ldap*), 18
- OPT_X_TLS_PROTOCOL_TLS1_2 (in module *ldap*), 18
- OPT_X_TLS_PROTOCOL_TLS1_3 (in module *ldap*), 18
- OPT_X_TLS_RANDOM_FILE (in module *ldap*), 18
- OPT_X_TLS_REQUIRE_CERT (in module *ldap*), 17
- OPT_X_TLS_REQUIRE_SAN (in module *ldap*), 17
- OPT_X_TLS_TRY (in module *ldap*), 17
- OPT_X_TLS_VERSION (in module *ldap*), 18
- OTHER, 21
- ## P
- PARAM_ERROR, 21
- parse() (*ldif.LDIFParser* method), 51

parse_entry_records() (*ldif.LDIFParser* RFC 1779, 39
 method), 51 RFC 2589, 41
 ParseLDIF() (*in module ldif*), 50 RFC 2696, 36
 PARTIAL_RESULTS, 21 RFC 2830, 29
 passwd() (*ldap.LDAPObject method*), 25 RFC 2849, 50
 passwd_s() (*ldap.LDAPObject method*), 25 RFC 3062, 26
 PasswordPolicyControl (*class in* RFC 3296, 35
 ldap.controls.ppolicy), 38 RFC 3829, 35
 PersistentSearchControl (*class in* RFC 3876, 36
 ldap.controls.psearch), 36 RFC 3909, 24
 PersistentSearchControl.PersistentSearchControl RFC 4370, 35
 (*class in ldap.controls.psearch*), 37 RFC 4422, 49
 PORT (*in module ldap*), 14 RFC 4512, 43
 postProcessing() (*ldap.asyncsearch.AsyncSearchHandler* RFC 4513, 49
 method), 31 RFC 4514, 39
 PostReadControl (*class in ldap.controls.readentry*), RFC 4515, 28, 41
 38 RFC 4516, 14, 52
 preProcessing() (*ldap.asyncsearch.AsyncSearchHandler* RFC 4527, 38
 method), 31 RFC 4528, 36
 PreReadControl (*class in ldap.controls.readentry*), RFC 4532, 29
 38 RFC 4533, 47
 processResults() (*ldap.asyncsearch.AsyncSearchHandler* RFC 6125, 17
 method), 31

PROTOCOL_ERROR, 21

ProxyAuthzControl (*class in ldap.controls.simple*), 35

R

ReadEntryControl (*class in* RFC 4515, 28, 41
 ldap.controls.readentry), 38 RFC 4516, 14, 52

ReconnectLDAPObject (*class in ldap.ldapobject*), 23

RefreshRequest (*class in ldap.extop.dds*), 41

RefreshRequest.RefreshRequestValue (*class in ldap.extop.dds*), 41

RefreshResponse (*class in ldap.extop.dds*), 41

RefreshResponse.RefreshResponseValue (*class in ldap.extop.dds*), 41

RelaxRulesControl (*class in ldap.controls.simple*), 35

rename() (*ldap.LDAPObject method*), 26

rename_s() (*ldap.LDAPObject method*), 26

RequestControl (*class in ldap.controls*), 33

RequestControlTuples() (*in module*
 ldap.controls), 34

ResponseControl (*class in ldap.controls*), 33

restart() (*slapdtest.SlapdObject method*), 55

result() (*ldap.LDAPObject method*), 26

result2() (*ldap.LDAPObject method*), 27

result3() (*ldap.LDAPObject method*), 27

result4() (*ldap.LDAPObject method*), 27

ResultProcessor (*class in ldap.resiter*), 42

RESULTS_TOO_LARGE, 21

RFC

S

sasl (*class in ldap.sasl*), 49

SASL_AVAIL (*in module ldap*), 14

SASL_BIND_IN_PROGRESS, 21

sasl_external_bind_s() (*ldap.LDAPObject*
 method), 27

sasl_gssapi_bind_s() (*ldap.LDAPObject*
 method), 27

sasl_interactive_bind_s() (*ldap.LDAPObject*
 method), 27

sasl_non_interactive_bind_s() (*ldap.LDAPObject*
 method), 27

SchemaElement (*class in ldap.schema.models*), 44

search() (*ldap.LDAPObject method*), 28

search_ext() (*ldap.LDAPObject method*), 28

search_ext_s() (*ldap.LDAPObject method*), 28

search_s() (*ldap.LDAPObject method*), 28

SEARCH_SCOPE (*in module ldapurl*), 52

SEARCH_SCOPE_STR (*in module ldapurl*), 52

search_st() (*ldap.LDAPObject method*), 28

server_class (*slapdtest.SlapdTestCase attribute*), 56

SERVER_DOWN, 21

SessionTrackingControl (*class in*
 ldap.controls.sessiontrack), 37

SessionTrackingControl.SessionIdentifierControlValue (*class in ldap.controls.sessiontrack*), 37

set_option() (*in module ldap*), 14

set_option() (*ldap.LDAPObject method*), 29

setup_rundir() (*slapdtest.SlapdObject method*), 55

setUpClass() (*slapdtest.SlapdTestCase class*
 method), 56

`simple_bind()` (*ldap.LDAPObject method*), 28
`simple_bind_s()` (*ldap.LDAPObject method*), 28
`SimpleLDAPObject` (*class in ldap.ldapobject*), 22
`SimplePagedResultsControl` (*class in ldap.controls.libldap*), 36
`SIZELIMIT_EXCEEDED`, 21
`slapadd()` (*slapdtest.SlapdObject method*), 55
`SlapdObject` (*class in slapdtest*), 55
`slapdtest` (*module*), 55
`SlapdTestCase` (*class in slapdtest*), 56
`start()` (*slapdtest.SlapdObject method*), 55
`start_tls_s()` (*ldap.LDAPObject method*), 29
`startSearch()` (*ldap.asyncsearch.AsyncSearchHandler method*), 31
`stop()` (*slapdtest.SlapdObject method*), 55
`str2dn()` (*in module ldap.dn*), 39
`STRONG_AUTH_NOT_SUPPORTED`, 22
`STRONG_AUTH_REQUIRED`, 22
`SubSchema` (*class in ldap.schema.subentry*), 43
`syncrepl_delete()` (*ldap.syncrepl.SyncreplConsumer method*), 47
`syncrepl_entry()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`syncrepl_get_cookie()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`syncrepl_poll()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`syncrepl_present()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`syncrepl_refreshdone()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`syncrepl_search()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`syncrepl_set_cookie()` (*ldap.syncrepl.SyncreplConsumer method*), 48
`SyncreplConsumer` (*class in ldap.syncrepl*), 47

T

`tearDownClass()` (*slapdtest.SlapdTestCase class method*), 56
`timeBeforeExpiration` (*ldap.controls.ppolicy.PasswordPolicyControl attribute*), 38
`TIMELIMIT_EXCEEDED`, 22
`TIMEOUT`, 22
`TLS_AVAIL` (*in module ldap*), 14
`tree()` (*ldap.schema.subentry.SubSchema method*), 44
`TYPE_OR_VALUE_EXISTS`, 22

U

`UNAVAILABLE`, 22
`UNAVAILABLE_CRITICAL_EXTENSION`, 22
`unbind()` (*ldap.LDAPObject method*), 29
`unbind_ext()` (*ldap.LDAPObject method*), 29
`unbind_ext_s()` (*ldap.LDAPObject method*), 29
`unbind_s()` (*ldap.LDAPObject method*), 29
`UNDEFINED_TYPE`, 22
`unparse()` (*ldapurl.LDAPUrl method*), 53
`unparse()` (*ldif.LDIFWriter method*), 51
`UNWILLING_TO_PERFORM`, 22
`update()` (*ldap.schema.models.Entry method*), 44
`urlfetch()` (*in module ldap.schema.subentry*), 43
`USER_CANCELLED`, 22

V

`ValueLessRequestControl` (*class in ldap.controls.simple*), 34

W

`wait()` (*slapdtest.SlapdObject method*), 56
`whoami_s()` (*ldap.LDAPObject method*), 29